



STATE OF IDAHO
DEPARTMENT OF
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, Idaho 83706 • (208) 373-0502

C.L. "Butch" Otter, Governor
Toni Hardesty, Director

May 25, 2007

Certified Mail No. 7005 1160 0000 1550 9231

Ron Smith
Plant Manager
Ash Grove Cement Company
230 Cement Road
Inkom, ID 83245

RE: Facility ID No. 005-00004, Ash Grove Cement Company, Inkom
Final PTC and Amended Tier I Operating Permit Letter

Dear Mr. Smith:

The Department of Environmental Quality (DEQ) is issuing Final PTCs No. P-060325 and amended Tier I Operating Permit No. TI-2007.0035, for changes to the kiln dust handling system at the Ash Grove Cement Co. (Ash Grove) facility located near Inkom, in accordance with IDAPA 58.01.01.209.05.c and 381, Rules for the Control of Air Pollution in Idaho. The Tier I permit has been administratively amended by DEQ as requested in your September 1, 2006, permit application. The Final PTC and the Amended Tier I permit are effective immediately. Please be aware these permits replace Section 15 of Tier II Operating Permit No. 005-00004, issued on November 27, 2002, and Tier I Operating Permit No. TI-060305 issued on November 6, 2006, the terms and conditions of which no longer apply. This permit does not release Ash Grove from compliance with all other applicable federal, state, or local laws, regulations, permits, or ordinances.

A representative of the Pocatello Regional Office will contact you regarding a meeting with DEQ to discuss the permit terms and requirements. DEQ recommends the following representatives attend the meeting: your facility's plant manager, responsible official, environmental contact, and any operations staff responsible for day-to-day compliance with permit conditions.

Pursuant to IDAPA 58.01.23, you, as well as any other entity, may have the right to appeal this final agency action within 35 days of the date of this decision. However, prior to filing a petition for a contested case, I encourage you to call Ken Hanna at (208) 373-0283 to address any questions or concerns you may have with the enclosed permit.

Sincerely,

A handwritten signature in black ink, appearing to read "Mike Simon".

Mike Simon, Stationary Source Program Manager
Air Quality Division

MS/KH/sm

Permit No.s P-060325 and TI-2007.0035

Enclosures

- c: Eric Hansen, Geomatrix Consultants, Inc., 19203 36th Avenue W, Suite 101, Lynwood, WA 98036
- Tom Edwards, Pocatello Regional Office
- Bill Rogers, Permit Coordinator (Ltr Only)
- Ken Hanna, Permit Writer (Ltr Only)
- Marilyn Seymore/ Pat Rayne, Air Quality Division
- Joan Lechtenberg, Public Comment
- Laurie Kral, US EPA Region 10
- Permit Binder
- Source File
- Phyllis Heitman (Ltr Only)
- Reading File (Ltr Only)



**Air Quality
PERMIT TO CONSTRUCT**

**State of Idaho
Department of Environmental Quality**

PERMIT NO.: P-060325

FACILITY ID No.: 005-00004

AQCR: 61

CLASS: A

SIC: 3241

ZONE: 12

UTM COORDINATE (km): 397.6 , 4738.6

1. PERMITTEE

Ash Grove Cement Co.

2. PROJECT

Kiln Dust Handling System

3. MAILING ADDRESS

230 Cement Road

CITY

Inkom

STATE

ID

ZIP

83245-1543

4. FACILITY CONTACT

Ron Smith

TITLE

PLANT MANAGER

TELEPHONE

(208) 775-3351

5. RESPONSIBLE OFFICIAL

Ron Smith

TITLE

Plant Manager

TELEPHONE

(208) 775-3351

6. EXACT PLANT LOCATION

230 Cement Road, Inkom

COUNTY

Bannock

7. GENERAL NATURE OF BUSINESS & KINDS OF PRODUCTS

Portland Cement Production

8. GENERAL CONDITIONS

This permit is issued according to IDAPA 58.01.01.200, Rules for the Control of Air Pollution in Idaho, and pertains only to emissions of air contaminants regulated by the state of Idaho and to the sources specifically allowed to be constructed or modified by this permit.

This permit (a) does not affect the title of the premises upon which the equipment is to be located; (b) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (c) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; (d) in no manner implies or suggests that the Department of Environmental Quality (DEQ) or its officers, agents, or employees, assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment.

This permit will expire if construction has not begun within two years of its issue date or if construction is suspended for one year.

This permit has been granted on the basis of design information presented with its application. Changes of design or equipment may require DEQ approval pursuant to the Rules for the Control of Air Pollution in Idaho, IDAPA 58.01.01.200, et seq.


KEN HANNA, PERMIT WRITER
DEPARTMENT OF ENVIRONMENTAL QUALITY


MIKE SIMON, STATIONARY SOURCE PROGRAM MANAGER
DEPARTMENT OF ENVIRONMENTAL QUALITY

DATE MODIFIED/REVISED:

DATE ISSUED:

May 25, 2007

Table Of Contents

ACRONYMS, UNITS, AND CHEMICAL NOMENCLATURES.....	3
1. PERMIT SCOPE.....	4
2. KILN DUST HANDLING.....	5
3. PERMIT TO CONSTRUCT GENERAL PROVISIONS.....	10

Acronyms, Units, And Chemical Nomenclatures

AQCR	Air Quality Control Region
CFR	Code of Federal Regulations
CKD	cement kiln dust
DEQ	Department of Environmental Quality
EPA	Environmental Protection Agency
ESP	electrostatic precipitator
hr	hour(s)
IDAPA	A numbering designation for all administrative rules in Idaho promulgated under the Idaho Administrative Procedures Act
km	kilometers
lb/hr	pound per hour
PM	particulate matter
PM ₁₀	particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers
PTC	permit to construct
SIP	State Implementation Plan
SIC	Standard Industrial Classification
T/yr	tons per year
yr	year(s)

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

1. PERMIT SCOPE

Purpose

- 1.1 This permit is issued as a modification to the November 27, 2002, Tier II operating permit and permit to construct and is not a renewal. The application for a Tier II renewal is currently being processed as a separate permitting action. This permit is a PTC action to modify the requirements for the kiln dust handling system.
- 1.2 This permit incorporates and replaces the following permit conditions in the Tier II Operating Permit No. 055-00004, PM₁₀ SIP Operating Permit, issued November 27, 2002, and these terms and conditions no longer apply:
- All conditions in Section 15, Cement Kiln Dust Handling

Regulated Sources

- 1.3 Table 1.1 below lists all sources of emissions that are regulated in this permit.

Table 1.1 SUMMARY OF REGULATED SOURCES

Permit Section(s)	Source Description	Emissions Control(s)
2	Kiln Dust Handling	Enclosures, bin vents

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

2. KILN DUST HANDLING

2.1 Process Description

The following information in conditions 2.1, 2.2, and 2.3 is a narrative description of the kiln dust handling system and the associated emission control systems regulated by this permit. This description is for informational purposes only.

The cement kilns produce two dust streams: multiclone dust and cement kiln dust. Multiclone dust is returned to the kilns as feed through the dust scoop systems. Cement kiln dust (CKD) is the dust removed by electrostatic precipitators (ESPs). This dust is higher in alkalis which can have a deleterious affect on cement. For this reason, CKD must at times be removed from the kiln system.

The two kilns are each equipped with multiclones and ESPs to remove dust from the kiln off-gases. Multiclone dust is transported with screw conveyors and elevators to the storage bin for the respective kiln. Kiln 1 and 2 multiclone dust storage bins are ventilated by baghouse #11. Multiclone dust is metered from these bins and returned to the kilns as feed.

CKD is produced from the ESPs and processed through two silos in series.

- (1) CKD silo 1. CKD silo 1 is a storage silo which receives CKD from both kilns by separate pneumatic conveyance systems. CKD is removed from this silo and pneumatically conveyed to CKD silo 2. Emissions from CKD silo 1 are controlled by a bin vent.
- (2) CKD silo 2. From CKD Silo 1, the CKD may be pneumatically transferred directly to CKD Silo 2 or blended with cement and then transferred to CKD Silo 2 prior to loadout into trucks and rail cars.

The loadout equipment will provide two options for loading railcars or trucks; loading dry product using a spout with an internal dust collection system (BH14); and using the "DustMaster" wetting system to load wetted CKD (15-20% moisture) into a truck. CKD may also be transported by vehicle to a 2 acre landfill pile.

Existing CKD conveying equipment, including screw conveyors, elevators, turbulator (wet paddle mixer) and dust bunkers, will be maintained as backup systems but not normally be used.

2.2 Emission Control Description

Emissions associated with the transfer of multiclone dust from the No. 1 and 2 multiclones to the dust bins are controlled by being enclosed. Emissions associated with kiln 1 and 2 multiclone bins are controlled by a baghouse (BH11).

Emissions associated with the transfer of CKD from the No. 1 and 2 kiln ESPs to CKD silos 1 and 2 are controlled by being enclosed. CKD Silos 1 and 2 use bin vents (fabric filters; BH12, BH13) to control emissions when air is displaced during filling.

Emissions from existing backup systems, which are not normally used, are controlled as follows: CKD emissions from the screw to the elevator, and from the elevator to a second screw are controlled by being enclosed.

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

2.3 Equipment Specifications

2.3.1 Baghouse No. 11 (BH11)

Manufacturer: Micro-Pulsaire
Model: Type 30-8
Equipment No.: 50-1212-000
Grain Loading: 0.01 gr/dscf (guaranteed), PM
Flowrate: 940 dscf

2.3.2 Bin Vent (baghouse) No. 12, CKD Silo 1 (BH12)

Grain Loading: 0.010 gr/dscf, PM/PM₁₀
Flowrate: 2400 dscf

2.3.3 Bin Vent (baghouse) No. 13, CKD Loadout Silo 2 (BH13)

Grain Loading: 0.010 gr/dscf, PM/PM₁₀
Flowrate: 1680 dscf

2.3.4 Fabric Filter, CKD Truck Loadout Spout (BH14)

Grain Loading: 0.010 gr/dscf, PM/PM₁₀
Flowrate: 1250 dscf

Emission Limits

2.4 PM and PM₁₀ Emission Limits - Baghouse BH11

The PM and PM₁₀ emissions from the stack of baghouse BH11 shall not exceed 0.014 grains per dry standard cubic foot (gr/dscf) based on a daily average.

[May 25, 2007]

2.5 PM and PM₁₀ Emission Limits - CKD Fabric Filters

The PM and PM₁₀ emissions from the stacks of BH12, BH13, and BH14 shall each not exceed 0.010 grains per dry standard cubic foot (gr/dscf) based on a daily average.

[May 25, 2007]

2.6 CKD Transfer Point Opacity Limit - NSPS

In accordance with 40 CFR 60.62(c), the permittee shall not cause to be discharged into the atmosphere from any affected facility any gases which exhibit 10% opacity, or greater. Affected facilities that are subject to this requirement include the following sources: the stacks of baghouses BH11, BH12, BH13, BH14; any screw conveyors associated with the dust scoop system; the dust feed spout (bulk loading systems); and any other conveyor transfer points, and bulk loading and unloading systems used to handle kiln dust. Opacity shall be determined using the procedures specified in 40 CFR 60.64(b) and IDAPA 58.01.01.625 (Rules for the Control of Air Pollution in Idaho).

[May 25, 2007]

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

2.7 Fugitive Dust Control Plan - CKD Handling Operations

All reasonable precautions shall be taken to prevent PM from becoming airborne while handling CKD as required in IDAPA 58.01.01.651. In determining what is reasonable, considerations will be given to factors such as the proximity of dust-emitting operations to human habitations and/or activities and atmospheric conditions that might affect the movement of PM. To establish reasonable precautions, the Permittee shall develop, maintain and implement a Fugitive Dust Control Plan for CKD handling operations which identifies potential sources of fugitive dust and which establishes good operating practices for limiting the formation and dispersion of dust from those sources. The approved Fugitive Dust Control Plan is part of the terms and conditions of the permit.

2.7.1 The Fugitive Dust Control Plan (Plan) shall contain, at a minimum, the following information and requirements with regard to CKD handling operations:

1. A general description of the potential sources of fugitive dust from the CKD handling operations.
2. Application of water from a water truck, or a suitable dust suppressant (e.g., magnesium chloride), for control of dust on haul roads and loading areas. The Plan must establish criteria to determine when water and/or dust suppressant must be applied. Water does not need to be applied when the surface is wet (i.e. during/following rainy conditions) or when reduced ambient temperatures may cause the water to freeze. The applicant may choose to use surface improvements to existing roads, such as paving, in lieu of water application where appropriate to control fugitive dust.
3. Procedures for installing and using hoods, fans, fabric filters, or equivalent systems, where practical, to enclose/capture and vent the handling of dusty materials.
4. Procedures for covering, open-bodied trucks transporting materials likely to give rise to airborne dusts, paving roadways, and maintaining them in a clean condition, where practical.
5. Procedures for promptly removing earth or other stored material from streets, where practical.
6. Procedures to minimize dust formation during conveying operations such as installing sides/covers on conveyors and transfer points, and minimizing material drop heights.
7. Procedures for conducting a weekly inspection of potential sources of fugitive emissions from the CKD handling operations during daylight hours and under normal operating conditions, to ensure that the methods used to reasonably control fugitive emissions are effective. If fugitive emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each weekly fugitive emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive emissions, and the date the corrective action was taken.
8. Training/orientation of employees about the Fugitive Dust Control Plan procedures.
9. The initial Fugitive Dust Control Plan shall be submitted to DEQ for review and approval no later than 30 days after the issuance date of this permit. After approval of the initial plan, the permittee may update the plan at any time by submitting the proposed changes to DEQ for review and approval. The updated plan shall not become effective until approved by DEQ.
10. When in operation, the permittee shall comply with the provisions in the approved Fugitive Dust Control Plan at all times. Whenever an operating parameter is outside the operating range specified by the plan, the permittee shall take corrective action as expeditiously as practicable to bring the operating parameter back within the operating range.
11. A copy of the Fugitive Dust Control Plan shall remain onsite at all times.

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

2.7.2 The permittee shall monitor and maintain records of the frequency and the method(s) used (i.e., water, chemical dust suppressants, etc.) to reasonably control fugitive emissions.

2.7.3 The permittee shall maintain records of all fugitive dust complaints received. The permittee shall take appropriate corrective action as expeditiously as practicable after receipt of a valid complaint. The records shall include, at a minimum, the date that each complaint was received and a description of the following: the complaint, the permittee's assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.

[May 25, 2007]

Operating Requirements

2.8 Monitoring Equipment

2.8.1 The permittee shall install, calibrate, maintain, and operate, in accordance with manufacturer specifications and the Dust Collector Maintenance Plan, equipment to continuously measure the pressure differential across each of the following air pollution control devices: BH11, BH12 and BH13.

2.8.2 For air pollution control device BH14, the permittee shall comply with one of the following options:

- Follow the requirements of Permit Condition 2.8.1; or
- Modify the Dust Collector Maintenance Plan to include specific procedures for performing a visible emissions observation of BH14, once per day, when in operation. The procedures shall set forth a specific minimum opacity trigger level for BH14 at which corrective action must be taken to comply with PTC General Provision 2.

[May 25, 2007]

2.9 Dust Collector Maintenance Plan

Within 60 days after startup of BH12, BH13 and BH14, the permittee shall have revised the Dust Collector Maintenance Plan to incorporate these new CKD baghouses. The Permittee shall operate and maintain all of the CKD baghouses (BH11, BH12, BH13, and BH14) in accordance with the Dust Collector Maintenance Plan. The Dust Collector Maintenance Plan shall describe the procedures that will be followed to comply with PTC General Provision 2 and the air pollution control device requirements contained in this permit. The plan shall remain on site at all times and shall be available to DEQ representatives upon request.

[May 25, 2007]

2.10 Pressure Drop Across Air Pollution Control Device

The pressure drop across air pollution control devices BH11, BH12 and BH13, and the pressure drop or opacity level of BH14, shall be maintained within the manufacturer and the Dust Collector Maintenance Plan's specifications. Documentation of both the manufacturer and Dust Collector Maintenance Plan's operating pressure drop specifications for each control device, and the minimum opacity trigger level for BH14 (if established under Permit Condition 2.8.2), shall remain on site at all times and shall be available to DEQ representatives upon request.

[May 25, 2007]

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

Monitoring and Recordkeeping Requirements

2.11 Baghouse Monitoring

The permittee shall record the pressure drop across baghouse BH11, BH12 and , BH13, and also across BH14 (if pressure drop is monitored under Permit Condition 2.8.1), on a weekly basis and record visual observations daily. The pressure drop shall be recorded as inches of water ("H₂O), in a log, kept at the facility for the most recent five year period. The log shall be made available to DEQ representatives upon request.

[May 25, 2007]

2.12 Initial Performance Test - NSPS

Within 60 days after achieving the maximum production rate at which the affected facility will be operated, but not later than 180 days after initial startup of such facility and at such other times as may be required by the Administrator under section 114 of the Act, the permittee shall conduct a performance test as required by 40 CFR 60.8 and 60.62(c), and in accordance with General Provision 6 of this permit and IDAPA 16.01.01.157, to demonstrate compliance with Permit Condition 2.6 of this permit. The affected facilities to be tested include the stacks of baghouses BH12, BH13, and BH14, and all new and modified conveyor transfer points with emissions to the atmosphere, and bulk loading and unloading systems used to handle CKD.

[May 25, 2007]

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

3. PERMIT TO CONSTRUCT GENERAL PROVISIONS

General Compliance

1. The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the Rules for the Control of Air Pollution in Idaho. The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit and the Rules for the Control of Air Pollution in Idaho, and the Environmental Protection and Health Act, Idaho Code §39-101, et seq.

[Idaho Code §39-101, et seq.]

2. The permittee shall at all times (except as provided in the Rules for the Control of Air Pollution in Idaho) maintain in good working order and operate as efficiently as practicable, all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.

[IDAPA 58.01.01.211, 5/1/94]

3. Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules and regulations.

[IDAPA 58.01.01.212.01, 5/1/94]

Inspection and Entry

4. Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:
 - a. Enter upon the permittee's premises where an emissions source is located or emissions related activity is conducted, or where records are kept under conditions of this permit;
 - b. Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
 - c. Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
 - d. As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

[Idaho Code §39-108]

Construction and Operation Notification

5. The permittee shall furnish DEQ written notifications as follows in accordance with IDAPA 58.01.01.211:
 - a. A notification of the date of initiation of construction, within five working days after occurrence;

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

- b. A notification of the date of any suspension of construction, if such suspension lasts for one year or more;
- c. A notification of the anticipated date of initial start-up of the stationary source or facility not more than sixty days or less than thirty days prior to such date;
- d. A notification of the actual date of initial start-up of the stationary source or facility within fifteen days after such date; and
- e. A notification of the initial date of achieving the maximum production rate, within five working days after occurrence - production rate and date.

[IDAPA 58.01.01.211, 5/1/94]

Performance Testing

- 6. If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ may, at its option, have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.

All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.

Within 30 days following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The written report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00]

Monitoring and Recordkeeping

- 7. The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Records of monitoring information shall include, but not be limited to the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

AIR QUALITY PERMIT TO CONSTRUCT NUMBER: P-060325

Permittee:	Ash Grove Cement Co.	Facility ID No. 005-00004
Location:	Inkom, Idaho	

Excess Emissions

8. The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions due to startup, shutdown, scheduled maintenance, safety measures, upsets and breakdowns.

[IDAPA 58.01.01.130-136, 4/5/00]

Certification

9. All documents submitted to DEQ, including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

False Statements

10. No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit, or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.125, 3/23/98]

Tampering

11. No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.126, 3/23/98]

Transferability

12. This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.

[IDAPA 58.01.01.209.06, 4/11/06]

Severability

13. The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.