



STATE OF IDAHO
DEPARTMENT OF
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, Idaho 83706 • (208) 373-0502

C.L. "Butch" Otter, Governor
Curt Fransen, Director

April 22, 2014

Bob Hall, Owner
H & B Crushing LLC
P.O. Box 117
Kuna, Idaho 83634

RE: Facility ID No. 777-00380, H & B Crushing LLC, Kuna
PR-2014.0020, Permit by Rule Registration Notification
Portable Rock Crushing Facility

Dear Mr. Hall:

The Department of Environmental Quality (DEQ) received a Permit by Rule Registration form on April 15, 2014 for a portable Nonmetallic Mineral Processing Plant from H & B Crushing LLC. The registration is for the following equipment, which includes all equipment currently registered for Facility ID No. 777-00380:

<u>Crushers</u>	<u>Screen Decks</u>	<u>Electrical Generators</u>
Manufacturer: Auston Western Type: Jaw Serial No.: 2036 82 Capacity (T/hr): 250 Year of Mfr.: early 1960s	Manufacturer: El Jay Size: 5'x16' Number of Decks: 3 Serial No.: 34CO793 Year of Mfr.: 1993	Manufacturer: Caterpillar Output (kW): 545 Fuel Type: Grade 2 Fuel Oil
Manufacturer: El Jay Type: Cone Serial No.: 2AH0193 Capacity (T/hr): 200 Year of Mfr.: 1993	Manufacturer: JCI Screen Size: 6'x20' Number of Decks: 3 Serial No.: 97H03K32 Year of Mfr.: 1997	Manufacturer: Stamford Output (kW): 75 Fuel Type: Grade 2 Fuel Oil
Manufacturer: VSI Texas Crusher Type: Not specified Serial No.: 99017 Capacity (T/hr): 300 Year of Mfr.: 1999	Manufacturer: El Jay Size: 6'x20' Number of Decks: 3 Serial No.: 39-GO891 Year of Mfr.: 1997	Manufacturer: Detroit Output (kW): 670 Fuel Type: Grade 2 Fuel Oil
Manufacturer: Crush Boss Type: Impact Serial No.: 5056539 Capacity (T/hr): 400 Year of Mfr.: Not Specified		
<u>Total Capacity¹ (T/hr)²</u>		
T/hr: 1,150		

¹ Per 40 CFR 60.771, Capacity means the cumulative rated capacity of all initial crushers that are part of the plant. Initial crusher means any crusher into which nonmetallic minerals can be fed without prior crushing in the plant.

² T/hr = tons per hour

**DEQ - AIR QUALITY PROGRAM
PERMIT BY RULE (PBR) REGISTRATION
For Nonmetallic Mineral Processing Plants**

RECEIVED
APR 15 2014
DEPARTMENT OF ENVIRONMENTAL QUALITY
STATE AQ PROGRAM

EQUIPMENT INFORMATION

Include in the tables below, all the equipment to be covered by this PBR registration:

ROCK CRUSHERS AND GRINDING MILLS

Crusher/Grinding Mill Type (jaw, cone, rod mill, etc.)	Manufacturer	Serial No.	Date of Manufacture	Maximum Throughput Capacity (tons per hour)
Impact Crusher	Crush Boss	5056539		400 tons
Detroit Gen	Detroit	GC 964164		670 tons

SCREEN DECKS


Manufacturer	Physical Size (length x width) (feet x feet)	No. of Decks	Serial No.	Date of Manufacture
EL JAY	6 X 20	3	39-60891	?

ELECTRICAL GENERATOR(S)

Manufacturer (Caterpillar, Onan, etc.)	Rated Output (kW)	Fuel Type (Grade 1 or 2 Fuel Oil)
Detroit	670	#2 FUEL

\$250 PBR registration fee enclosed

Certification of Truth, Accuracy, and Completeness (by Responsible Official)
I hereby certify that based on information and belief formed after reasonable inquiry, the statements and information contained in this and any attached and/or referenced document(s) are true, accurate, and complete in accordance with IDAPA 58.01.01.123-124.


 Responsible Official Signature

OWNER
 Responsible Official Title

4-14-14
 Date

Bob Hall
 Print or Type Responsible Official Name

**DEQ - AIR QUALITY PROGRAM
 PERMIT BY RULE (PBR) REGISTRATION
 For Nonmetallic Mineral Processing Plants**

Please be sure to read the instructions on page 1 prior to completing this registration form.

GENERAL INFORMATION

Company Name:	Hv B Crushing LLC		
Mailing Address:	P.O. Box 117		
City:	Kuna	State:	ID
Zip Code:	83634	County:	Oda
General Nature of Business & Products:	Portable Rock Crushing		

Contact Name, Title:	Bob Hall		
Phone:	208-362-7477	Cell:	208-866-3461
Email:	hbcushing@yahoo.com		

Owner or Responsible Official Name, Title:	Bob Hall, owner		
Phone:	208-362-7477		
Email:	hbcushing@yahoo.com		

Proposed Initial Plant Location:	1700 E. Yam Hill Boise ID		
Nearest City:	Boise	Estimated Startup Date:	4-18-14
County:	Oda		

Reason for Application:	<input type="checkbox"/> Register an unpermitted/unregistered source
	<input type="checkbox"/> Cancel a permit and obtain a PBR
	<input checked="" type="checkbox"/> Add, remove, or edit equipment listed on existing Permit By Rule

If the equipment included in this registration is currently permitted, you must request the cancellation of the current permit(s) by completing the following:

PERMITS TO BE CANCELLED

Permit Type (PTC, Tier II)	Permit No.	Permit Issuance Date

Comments:



Form must be submitted ten (10) days before plant is relocated. (IDAPA 58.01.01.500.01)

Facility Information

- 1. Facility Name:
2. Facility ID Number: (This number can be found on the first page of your DEQ permit/PBR.)
3. Mailing Address (street/city/state/zip):
4. Facility Contact Name & Title:
5. Facility Contact Phone:
6. Responsible Official Name & Title:
7. Responsible Official Signature:
Date:

In accordance with IDAPA 58.01.01.123 (Rules for the Control of Air Pollution in Idaho), by signing, I certify based on information and belief formed after reasonable inquiry, the statements and information in this document(s) are true, accurate, and complete. (The responsible official is defined in IDAPA 58.01.01.006.99.)

Equipment

- 8. Plant Type:
Hot Mix Asphalt
Rock Crusher
Concrete Batch
Other
If Other, Describe:

Permit

- 9. Permit Type:
Permit To Construct (PTC)
Operating Permit (OP)
Permit By Rule (PBR)
Exempt
None
10. Permit / PBR Number:
11. Date Issued:

Current Location

- 12. Current Idaho County:
13. Nearest City:
14. GPS Coordinates (WGSG4 format):
UTM X (easting) (km)
UTM Y (northing) (km)
15. Describe Current Location:
In Storage/Idle
Out Of State
Other
If Other, Describe:
16. How long has plant operated at current location?

New Location

- 17. New Idaho County:
18. Nearest City:
19. GPS Coordinates (WGSG4 format):
UTM X (easting) (km)
UTM Y (northing) (km)
20. Describe New Location:
In Storage/Idle
Out Of State
Other
If Other, Describe:
21. Estimated Start Date:
22. Estimated End Date:

Additional Information

Empty box for additional information.

SUBMIT:
via E-mail: aqperf@deq.idaho.gov
Subject: PERF Submittal
Complete form, sign it, and attach to E-mail
or via FAX: 208-373-0340
To: Air Quality Program
Regarding: PERF Submittal
or via Mail: Air Quality - PERF Processing
Dept. of Environmental Quality
1410 North Hilton
Boise, ID 83706-1255

Print Form

b. One (1) hour of operation representing worst-case conditions for the emissions of particulate matter. (4-5-00)

03. **Test Methods and Procedures.** The appropriate test method under Sections 785 through 788 shall be EPA Method 5 contained in 40 CFR Part 60 or such comparable and equivalent methods approved in accordance with Subsection 157.02.d. Test methods and procedures shall comply with Section 157. (4-5-00)

787. EXCEPTIONS.

Sections 785 and 786 do not apply to wigwam burners. (3-23-98)

788. — 789. (RESERVED)

790. RULES FOR THE CONTROL OF NONMETALLIC MINERAL PROCESSING PLANTS.

The purpose of Sections 790 through 799 is to set forth the requirements for nonmetallic mineral processing plants, frequently referred to as rock crushers. Definitions specific to nonmetallic mineral processing permits are located in Section 011 while other general terms may be defined in Sections 006 through 008. Compliance with Section 790 does not relieve the owner or operator of a nonmetallic mineral processing plant from the responsibility of complying with other federal, state, and local applicable laws, regulations, and requirements. (3-15-02)

791. GENERAL CONTROL REQUIREMENTS.

01. **Prohibition.** No owner or operator of a nonmetallic mineral processing plant shall allow, suffer, or cause the emissions of any air pollutant to the atmosphere in such quantity of such nature and duration and under such conditions as would be injurious to human health or welfare, to animal or plant life, or to property, or to interfere unreasonably with the enjoyment of life or property. (3-15-02)

02. **Control of Fugitive Dust.** In accordance with Sections 650 and 651, owners and operators of nonmetallic mineral processing plants shall take all reasonable precautions to prevent the generation of fugitive dust. In determining what is reasonable, consideration will be given to factors such as the proximity to human habitations and/or activities and atmospheric conditions which might affect the movement of particulate matter. (3-15-02)

792. EMISSIONS STANDARDS FOR NONMETALLIC MINERAL PROCESSING PLANTS SUBJECT TO 40 CFR 60, SUBPART 000.

01. **Applicability and Designation of Affected Facilities.** The provisions of 40 CFR 60.670(a)(1) are applicable to the following affected facilities in fixed or portable nonmetallic mineral processing plants that commence construction, modification, or reconstruction after August 31, 1983: each crusher, grinding mill, screening operation, bucket elevator, belt conveyor, bagging operation, storage bin, and enclosed truck or railcar loading station. Also, crushers and grinding mills at hot mix asphalt facilities that reduce the size of nonmetallic minerals embedded in recycled asphalt pavement and subsequent affected facilities up to, but not including the first storage silo or bin, are subject to the provisions of 40 CFR 60.670(a)(1). (4-4-13)

02. **Facilities Not Applicable to 40 CFR 60.670(a)(2), (b), and (c).** The provisions of 40 CFR 60.670(a)(2), (b), and (c) do not apply to the following operations: all facilities located in underground mines, plants without crushers or grinding mills above ground, and wet processing operations (as defined in 40 CFR 60.671). (4-4-13)

a. An affected facility that is subject to the provisions of 40 CFR 60, Subpart F (Standards of Performance for Portland Cement Plants) or Subpart I (Standards of Performance for Hot Mix Asphalt Plants) or that follows the in plant process any facility subject to the provisions of 40 CFR 60, Subparts F or I, is not subject to the provisions of 40 CFR 60, Subpart 000. (4-4-13)

b. Facilities at the following plants are not subject to the provisions of 40 CFR 60, Subpart 000: (4-4-13)

i. Fixed sand and gravel plants and crushed stone plants with capacities, as defined in 40 CFR 60.671,

of twenty-three (23) megagrams per hour (twenty-five (25) tons per hour) or less; (4-4-13)

ii. Portable sand and gravel plants and crushed stone plants with capacities, as defined in 40 CFR 60.671, of one hundred thirty-six (136) megagrams per hour (one hundred fifty (150) tons per hour) or less; and (4-4-13)

iii. Common clay plants and pumice plants with capacities, as defined in 40 CFR 60.671, of nine (9) megagrams per hour (ten (10) tons per hour) or less. (4-4-13)

03. Standards of Performance for Nonmetallic Mineral Processing Plants. Affected facilities subject to 40 CFR 60, Subpart OOO, shall comply with all applicable emissions standards, monitoring requirements, test methods and procedures, and reporting and recordkeeping requirements. (4-4-13)

793. EMISSIONS STANDARDS FOR NONMETALLIC MINERAL PROCESSING PLANTS NOT SUBJECT TO 40 CFR 60, SUBPART OOO.

Owners and operators of nonmetallic mineral processing plants that are not subject to a NSPS requirement shall comply with the emissions standards set forth in Section 793. (3-15-02)

01. Processing Plants Not Regulated by NSPS. Fixed or portable plants that commenced construction, reconstruction, or modification before August 31, 1983 are not subject to 40 CFR 60, Subpart OOO. (3-15-02)

02. Emissions Standards for Fugitive Emissions. No owner or operator shall cause to be discharged into the atmosphere emissions which exhibit greater than twenty percent (20%) opacity from any crusher, grinding mill, screening operation, bucket elevator, belt conveyor, conveying system, transfer point, vent, capture system, storage bin, stockpile, truck dumping operation, vehicle traffic on an affected paved public roadway, vehicle traffic on or wind erosion of an unpaved haul road, or other source of fugitive emissions. Opacity shall be determined using the test methods and procedures in Section 625. The plant is not required to have a certified opacity reader. (3-15-02)

794. PERMIT REQUIREMENTS.

No owner or operator may commence construction, reconstruction, modification or operation of any nonmetallic mineral processing plant regardless of whether or not the source is an affected facility pursuant to 40 CFR 60.670(e) without first obtaining a permit or complying with Sections 795 through 799. The owner or operator shall comply with the permitting requirements of Subsection 794.01 or Subsection 794.02 and the applicable portions of Subsection 794.03 and/or Subsection 794.04. (4-4-13)

01. Permit by Rule. Owners and operators of nonmetallic mineral processing plants that meet all of the applicable requirements set forth in Sections 795 through 799 shall be deemed to have a permit by rule (PBR) and shall not be required to obtain a permit to construct under Sections 200 through 228. (3-15-02)

02. Permit to Construct. Owners and operators of nonmetallic mineral processing plants that do not meet all of the requirements set forth in Sections 795 through 799, or that operate or intend to operate a nonmetallic mineral processing plant at a single site of operations for more than twelve (12) consecutive months, or that choose to construct and operate under specific permit requirements rather than the provisions of the permit by rule shall obtain a permit to construct pursuant to Sections 200 through 228. An existing permit to construct shall be considered valid until the permit is modified, incorporated into a Tier II operating permit, or terminated by the Department. Existing permits to construct may be terminated by the Department by registering the source under the permit by rule provisions in accordance with Section 797 after June 15, 2001. (3-15-02)

03. Tier I Operating Permits. Owners and operators of nonmetallic mineral processing plants that are affected facilities subject to a requirement of the New Source Performance Standards (NSPS) in 40 CFR 60 are Tier I sources as defined in Section 006. Tier I sources must comply with the applicable permitting requirements of Sections 300 through 399. (4-11-06)

04. Tier II Operating Permits. Owners and operators of nonmetallic mineral processing plants that are required by the Department or choose to obtain a Tier II operating permit pursuant to Sections 400 through 410 shall operate in accordance with the specific provisions of the Tier II operating permit until such time as the operating

permit is terminated in writing by the Department. The Department may require owners and operators of nonmetallic mineral processing plants to obtain a Tier II operating permit whenever the Department determines that: (3-15-02)

a. Emission rate reductions are necessary to attain or maintain any ambient air quality standard or applicable prevention of significant deterioration (PSD) increment; or (3-15-02)

b. Specific emissions standards, or requirements on operation or maintenance are necessary to ensure compliance with any applicable emission standard or rule. (3-15-02)

795. PERMIT BY RULE REQUIREMENTS.

The purpose of Sections 795 through 799 is to establish the requirements for a permit by rule for nonmetallic mineral processing plants. (3-15-02)

796. APPLICABILITY.

01. **Permit by Rule.** Owners and operators of nonmetallic mineral processing plants shall be deemed to have a permit by rule if they comply with all of the applicable provisions of Sections 795 through 799. Nothing in Sections 795 through 799 shall preclude any owner or operator from obtaining a permit. Portable sources that operate or may be operated at a single location or site of operations for more than twelve (12) consecutive months must obtain a permit to construct or a Tier II operating permit. (3-15-02)

02. **Permit Option.** Owners and operators of nonmetallic mineral processing plants that hold a valid permit to construct or a Tier II operating permit must comply with the terms and conditions of the permit and are not subject to the requirements of the permit by rule in Sections 795 through 799. (3-15-02)

797. REGISTRATION FOR PERMIT BY RULE.

01. **Registration Process.** Any owner or operator of a nonmetallic mineral processing plant that opts to operate under the permit by rule shall register in the following manner: (3-15-02)

a. Any new or modified processing plant shall register fifteen (15) days prior to commencing operation or modification. The Department shall acknowledge registration in writing within fifteen (15) days. (3-15-02)

b. Any permitted processing plant shall register with the Department and request termination of the current permit to construct or Tier II operating permit. The Department shall normally act on the request within fifteen (15) days and notify the registrant in writing. (3-15-02)

Registration for permit by rule does not relieve the owner or operator of portable equipment from the registration and relocation requirements of Section 500. (3-15-02)

02. **Registration Information.** The following information shall be provided by the registrant to the Department: (3-15-02)

a. For all crushers and grinding mills, the registrant shall supply information on the manufacturer, crusher type (such as jaw, cone), serial number, date of manufacture, and maximum throughput capacity; (3-15-02)

b. For all screen decks, the registrant shall supply manufacturer name, physical size of screen, number of decks, serial number, and date of manufacture; and (3-15-02)

c. For all electrical generators, the registrant shall supply manufacturer name, rated output, and fuel. (3-15-02)

798. ELECTRICAL GENERATORS.

The following requirements apply to all electrical generators used to provide electrical power to any nonmetallic mineral processing plant. The requirements apply to each site of operations. (3-15-02)

01. **Fuel Type.** Only ASTM (American Society of Testing and Materials) Grade 1 or 2 fuel oil shall be used. The sulfur content of the fuel used shall not exceed the percentages of sulfur given in Section 725. (5-8-09)

02. **Generator Operating Requirements.** For the purposes of Sections 790 through 799, the following apply to all electrical generators.

Rated Output Capacities (kW)	Allowable Operating Hours (hr/day)		Allowable Operating Hours (hr/yr)	
	Attainment Unclassifiable Areas	PM-10 Nonattainment Areas	Attainment Unclassifiable Areas	PM-10 Nonattainment Areas
0 - 454	24	8	8760	2880
455 - 1000	24	24	8760	8760
1001 - 2000	24	24	5200	5200

kW = kilowatts
 hr/day = hours per day
 hr/yr = hours per year

(3-15-02)

03. **Generator Opacity Limit.** Visible emissions from any generator stack, vent, or other functionally equivalent opening shall not exceed twenty percent (20%) opacity for a period or periods aggregating more than three (3) minutes in any sixty (60) minute period. Opacity shall be determined using the test methods and procedures contained in Section 625.

(3-15-02)

04. **Monitoring and Recordkeeping Requirements.**

(3-15-02)

a. The owner or operator shall monitor and record the following information.

(3-15-02)

i. The rated output capacity, in kilowatts (kW), of the electrical generator(s) used;

(3-15-02)

ii. Operating hours on a monthly and annual basis so compliance can be continuously determined for the previous twelve (12) month period; and

(3-15-02)

iii. Vendor receipts of the fuel oil purchased clearly identifying the ASTM Grade.

(3-15-02)

b. Records of monitoring and recordkeeping requirements for current operations shall be maintained at the site of operations for the duration of operations at that location and shall be available to Department representatives upon request. Records for previous sites of operation shall be kept for the most recent two (2) year period at a location where they can be reasonably accessed and shall be made available to the Department upon request.

(3-15-02)

799. NONMETALLIC MINERAL PROCESSING PLANT FUGITIVE DUST BEST MANAGEMENT PRACTICE.

The owner or operator of a nonmetallic mineral processing plant shall use the Best Management Practices (BMP) contained in Section 799 to control the emissions of fugitive dust. Fugitive dust emissions shall be reasonably controlled as required by Sections 650 and 651. It shall be the responsibility of the owner or operator to reasonably control fugitive emissions at each site of operations but only for the duration of operations at each site under the control of the owner or operator.

(3-15-02)

01. **Generally Applicable Requirements.** All reasonable precautions shall be taken to prevent particulate matter from becoming airborne. The following requirements apply generally to this Fugitive Dust BMP.

(3-15-02)

a. Control strategy triggers. The owner or operator of a nonmetallic mineral processing plant shall at all times be observant of all sources of fugitive dust emissions and monitor control strategies at least once per day when operating. When fugitive dust emissions are observed at any time to be exceeding any control strategy trigger specified in Subsections 799.02 through 799.06, that event shall trigger initiation of the prescribed control strategy or control strategies to control the fugitive dust emissions. (3-15-02)

b. Control strategies. A progressive control strategy shall be used to reasonably control the emissions of fugitive dust. Progressive control strategy means that if the initial control strategy or strategies chosen do not adequately control fugitive dust emissions, the owner or operator shall employ successive control strategies as listed until fugitive dust control is achieved. Fugitive dust control shall be applied on a frequency such that visible emissions do not exceed any emission standard specified in Sections 790 through 799. (3-15-02)

c. Monitoring and recordkeeping. The owner or operator shall maintain a record of each event where a control strategy is triggered. The trigger shall be recorded with a summary of the control strategy employed. If the trigger is a citizen complaint, the owner or operator shall record the complaint, an evaluation of whether the complaint has merit, and a summary of the corrective action taken. The record shall be maintained on forms provided by the Department or other forms that contain similar information. Records for current operations shall be maintained at the site of operations for the duration of operations at that location and shall be available to Department representatives upon request. Records for previous sites of operation shall be kept for the most recent two (2) year period at a location where they can be reasonably accessed and shall be made available to the Department upon request. (3-15-02)

02. Requirements for Paved Public Roadways. (3-15-02)

a. Definitions. (3-15-02)

i. Paved public roadway. A paved public roadway means a roadway accessible to the general public having a surface of asphalt or concrete. (3-15-02)

ii. Track-out. Track-out means the deposition of mud, dirt, or similar debris onto the surface of a paved public roadway from the tires and/or undercarriage of any vehicle associated with the operation of a nonmetallic mineral processing plant. (3-15-02)

b. Control strategy triggers. Triggers that require initiation of a strategy or strategies to control fugitive dust emissions from track-out include, but are not limited to: (3-15-02)

i. Visible deposition of mud, dirt, or similar debris on the surface of a paved public roadway. (3-15-02)

ii. Visible fugitive emissions from vehicle traffic on an affected paved public roadway that approach twenty percent (20%) opacity for a period or periods aggregating more than one (1) minute in any sixty (60) minute period. (3-15-02)

iii. Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

c. Control strategies. The following are control strategies for track-out. (3-15-02)

i. Prompt removal of mud, dirt, or similar debris from the affected surface of a paved public roadway. (3-15-02)

ii. Water flush, and/or water flush and vacuum sweep, the affected surface of the paved public roadway. Runoff shall be controlled so it does not saturate the surface of the adjacent unpaved haul road such that track-out is enhanced. If runoff is not, or cannot be controlled, gravel shall be applied to the surface of the adjacent

unpaved haul road over an area sufficient to control track-out. (3-15-02)

iii. Apply gravel to the surface of the adjacent unpaved haul road. The area of application shall be sufficient to control track-out. (3-15-02)

iv. Apply an environmentally safe chemical soil stabilizer or chemical dust suppressant to the surface of the adjacent unpaved haul road. The area of application shall be sufficient to control track-out. (3-15-02)

v. Other control strategy or strategies as approved by the Department. (3-15-02)

03. Requirements for Unpaved Haul Roads. (3-15-02)

a. Definition of "unpaved haul roads." Any unsurfaced roadway within the physical boundary of a nonmetallic mineral processing facility that is used as a haul road, access road, or similar. (3-15-02)

b. Control strategy triggers. Triggers that require initiation of a strategy or strategies to control fugitive dust emissions from unpaved haul roads include, but are not limited to: (3-15-02)

i. Visible fugitive emissions from vehicle traffic on an affected paved public roadway that approach twenty percent (20%) opacity for a period or periods aggregating more than one (1) minute in any sixty (60) minute period. (3-15-02)

ii. Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

c. Control strategies. The following are control strategies for fugitive dust emissions from unpaved haul roads. (3-15-02)

i. Limit vehicle traffic on unpaved haul roads. (3-15-02)

ii. Limit vehicle speeds on unpaved haul roads. If a speed limit is imposed, signs shall be posted along the haul road route and clearly indicate the speed limit. Signs shall be placed so they are visible to vehicles entering and leaving the site of operations. (3-15-02)

iii. Apply water to the surface of the unpaved haul road. Runoff shall be controlled so it does not saturate the surface of the unpaved haul road such that it causes track-out. If runoff is not, or cannot be controlled, gravel shall be applied to the surface of the unpaved haul road over an area sufficient to control track-out. (3-15-02)

iv. Apply gravel to the surface of the unpaved haul road. (3-15-02)

v. Apply an environmentally safe chemical soil stabilizer or chemical dust suppressant to the surface of the unpaved haul road. (3-15-02)

vi. Other control strategy or strategies as approved by the Department. (3-15-02)

04. Requirements for Transfer Points, Screening Operations, and Stacks and Vents. (3-15-02)

a. Definitions. (3-15-02)

i. Transfer point. Transfer point means a point in a conveying operation where the nonmetallic mineral is transferred to or from a belt conveyor except where the nonmetallic mineral is being transferred to a stockpile. (3-15-02)

ii. Belt conveyor. Belt conveyor means a conveying device that transports material from one (1)

location to another by means of an endless belt that is carried on a series of idlers and routed around a pulley at each end. (3-15-02)

iii. Conveying system. Conveying system means a device for transporting materials from one (1) piece of equipment or location to another location within a plant. Conveying systems include but are not limited to the following: feeders, belt conveyors, bucket elevators and pneumatic systems. (3-15-02)

iv. Bucket elevator. Bucket elevator means a conveying device of nonmetallic minerals consisting of a head and foot assembly which supports and drives an endless single or double strand chain or belt to which buckets are attached. (3-15-02)

v. Screening operation. Screening operation means a device for separating material according to size by passing undersize material through one (1) or more mesh surfaces (screens) in series, and retaining oversize material on the mesh surfaces (screens). (3-15-02)

vi. Capture system. Capture system means the equipment (including enclosures, hoods, ducts, fans, dampers, etc.) used to capture and transport particulate matter generated by one (1) or more process operations to a control device. (3-15-02)

vii. Control device. Control device means the air pollution control equipment used to reduce particulate matter emissions released to the atmosphere from one (1) or more process operations at a nonmetallic mineral processing plant. (3-15-02)

viii. Vent. Vent means an opening through which there is mechanically induced air flow for the purpose of exhausting from a building air carrying particulate matter emissions from one (1) or more affected facilities. (3-15-02)

b. Control strategy triggers. Triggers that require initiation of a strategy or strategies to control fugitive dust emissions from transfer points, belt conveyors, bucket elevators, screening operations, conveying systems, capture systems, and building vents include, but are not limited to, the following: (3-15-02)

i. NSPS regulated processing plants. (3-15-02)

(1) Opacity greater than ten percent (10%) from any transfer point on a belt conveyor, conveying system, bucket elevator, or screening operation. (3-15-02)

(2) For any transfer point on a belt conveyor, conveying system, bucket elevator, or screening operation located within a building, opacity greater than seven percent (7%) from any building vent. (3-15-02)

(3) Opacity greater than seven percent (7%) from any capture system stack. (3-15-02)

(4) Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

ii. Processing plants not regulated by NSPS. (3-15-02)

(1) Opacity greater than twenty percent (20%) from any transfer point on a belt conveyor, conveying system, bucket elevator, or screening operation. (3-15-02)

(2) For any transfer point on a belt conveyor, conveying system, bucket elevator, or screening operation located within a building, opacity greater than twenty percent (20%) from any building vent. (3-15-02)

(3) Opacity greater than twenty percent (20%) from any capture system stack. (3-15-02)

(4) Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

c. Control Strategies. The following are control strategies for transfer points, belt conveyors, bucket elevators, screening operations, conveying systems, capture systems, and building vents. Controls shall be applied on a frequency such that visible fugitive emissions do not exceed any applicable opacity limit. (3-15-02)

i. Limit drop heights of materials such that there is a homogeneous flow of material. (3-15-02)

ii. Install, operate, and maintain water spray bars to control fugitive dust emissions at transfer points on belt conveyors, conveying systems, bucket elevators, and screening operations as necessary. (3-15-02)

iii. Other control strategy or strategies as approved by the Department. (3-15-02)

05. Requirements for Crushers and Grinding Mills. (3-15-02)

a. Definitions. (3-15-02)

i. Crusher. Crusher means a machine used to crush any nonmetallic mineral, and includes, but is not limited to, the following types: jaw, gyratory, cone, roll, rod mill, hammermill, and impactor. (3-15-02)

ii. Grinding mill. Grinding mill means a machine used for the wet or dry fine crushing of any nonmetallic mineral. Grinding mills include, but are not limited to, the following types: hammer, roller, rod, pebble and ball, and fluid energy. The grinding mill includes the air conveying system, air separator, or air classifier, where such systems are used. (3-15-02)

iii. Initial crusher. Initial crusher means any crusher into which nonmetallic minerals can be fed without prior crushing in the plant. (3-15-02)

b. Control strategy triggers. Triggers that require initiation of a strategy or strategies to control fugitive dust emissions from any crusher, grinding mill, building vent, or capture system stack include, but are not limited to, the following. (3-15-02)

i. NSPS regulated processing plants. (3-15-02)

(1) Opacity greater than fifteen percent (15%) from any crusher or grinding mill at which capture system is not used. (3-15-02)

(2) For any crusher or grinding mill located within a building, opacity greater than seven percent (7%) from any building vent. (3-15-02)

(3) Opacity greater than seven percent (7%) from any capture system stack. (3-15-02)

(4) Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

ii. Processing plants not regulated by NSPS. (3-15-02)

(1) Opacity greater than twenty percent (20%) from any crusher or grinding mill at which capture system is not used. (3-15-02)

(2) For any crusher or grinding mill located within a building, opacity greater than twenty percent (20%) from any building vent. (3-15-02)

(3) Opacity greater than twenty percent (20%) from any capture system stack. (3-15-02)

(4) Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

c. Control strategies. The following are control strategies for any crusher, grinding mill, building vent, or capture system stack. Controls shall be applied on a frequency such that visible fugitive emissions do not exceed any applicable opacity limit. (3-15-02)

i. Limit drop heights of materials such that there is a homogeneous flow of material. (3-15-02)

ii. Install, operate, and maintain water spray bars to control fugitive dust emissions at crusher drop points as necessary. (3-15-02)

iii. Other control strategy or strategies as approved by the Department. (3-15-02)

06. Requirements for Stockpiles. (3-15-02)

a. Definitions. (3-15-02)

i. Stockpile. Stockpile means any nonmetallic mineral storage pile, reserve supply, or similar. Nonmetallic minerals shall have the meaning given in 40 CFR Part 60, Subpart OOO. Nonmetallic minerals may be stockpiled by belt conveyor, truck dumping, or similar. (3-15-02)

ii. Truck dumping. Truck dumping means the unloading of nonmetallic minerals from movable vehicles designed to transport nonmetallic minerals from one (1) location to another. Movable vehicles include but are not limited to: trucks, front-end loaders, skip hoists, and railcars. (3-15-02)

b. Control strategy triggers. Triggers that require immediate initiation of a strategy or strategies to control fugitive dust emissions from stockpiles include, but are not limited to: (3-15-02)

i. Visible fugitive emissions from wind erosion of any stockpile that approaches twenty percent (20%) opacity for a period or periods aggregating more than one (1) minute in any sixty (60) minute period. (3-15-02)

ii. Citizen complaints of failure to reasonably control fugitive dust shall be expeditiously evaluated by the owner or operator for merit. If the owner or operator determines the complaint has merit, the progressive strategy shall be expeditiously employed to reasonably control fugitive dust. The Department may review the complaint records and investigate citizen complaints as appropriate. If the Department finds that a complaint has merit, it may determine additional control measures are required. (3-15-02)

c. Control strategies. The following are control strategies for stockpiles. (3-15-02)

i. Limit the height of the stockpiles. (3-15-02)

ii. Limit the disturbance of the stockpiles. (3-15-02)

iii. Apply water onto the surface of the stockpile. (3-15-02)

iv. Other control strategy or strategies as approved by the Department. (3-15-02)

800. REGISTRATION FEE FOR PERMIT BY RULE.

A registration fee of two hundred fifty dollars (\$250) shall be submitted to the Department with each permit by rule registration. (7-1-02)

801. PAYMENT OF FEES FOR PERMITS BY RULE REGISTRATION.

The permit by rule registration fee shall be paid in its entirety at the time the required registration form is submitted to the Department. The permit by rule registration form and fee should be sent to:

Permit by Rule Registration Fees
Fiscal Office
Idaho Department of Environmental Quality
1410 N. Hilton, Boise, ID 83706-1255

(7-1-02)

802. RECEIPT AND USAGE OF FEES.

Permit by rule registration fee receipts shall be deposited by the Department into a stationary source permit account. Monies from this account shall be used solely toward technical, legal and administrative support of the Department's Permit to Construct and Tier II permit programs and shall not be used for those activities supported by the fund created for implementing the operating permit program required under Title V of the federal Clean Air Act amendments of 1990. Fees payable under Section 800 shall be retained by the Department regardless of whether a permit by rule registration is accepted by the Department in response to a registration request. (7-1-02)

803. -- 804. (RESERVED)

805. RULES FOR CONTROL OF HOT-MIX ASPHALT PLANTS.

The purpose of Sections 805 through 808 is to establish for hot-mix asphalt plants restrictions on the emission of particulate matter. (5-1-94)

806. EMISSION LIMITS.

No person shall cause, allow or permit a hot-mix asphalt plant to have particulate emissions which exceed the limits specified in Sections 700 through 703. (5-1-94)

807. MULTIPLE STACKS.

In the case of more than one (1) stack to a hot-mix asphalt plant, the emission limitation will be based on the total emission from all stacks. (5-1-94)

808. FUGITIVE DUST CONTROL.

01. Fugitive Emission Controls. No person shall cause, allow or permit a plant to operate that is not equipped with an efficient fugitive dust control system. The system shall be operated and maintained in such a manner as to satisfactorily control the emission of particulate material from any point other than the stack outlet. (5-1-94)

02. Plant Property Dust Controls. The owner or operator of the plant shall maintain fugitive dust control of the plant premises and plant owned, leased or controlled access roads by paving, oil treatment or other suitable measures. Good operating practices, including water spraying or other suitable measures, shall be employed to prevent dust generation and atmospheric entrainment during operations such as stockpiling, screen changing and general maintenance. (5-1-94)

809. -- 814. (RESERVED)

815. RULES FOR CONTROL OF KRAFT PULP MILLS.

The purpose of Sections 815 through 818 is to establish emission standards for recovery furnaces and notification and reporting requirements for low volume high concentration (LVHC) and high volume low concentration (HVLC) gas venting at kraft pulp mills. (3-29-12)

816. RECOVERY FURNACE TRS STANDARD.

The average daily emissions of total reduced sulfur (TRS) from each recovery furnace shall not exceed fifteen (15)