



STATE OF IDAHO  
DEPARTMENT OF  
ENVIRONMENTAL QUALITY

1410 NORTH HILTON, BOISE, ID 83706 • (208) 373-0502

C. L. "BUTCH" OTTER, GOVERNOR  
JOHN H. TIPPETS, DIRECTOR

August 17, 2015

VIA EMAIL

Jon Reeder, General Manager  
Trails West Manufacturing of Idaho  
P. O. Box 67  
Preston, ID 83263

RE: Facility ID No. 041-00022, Trails West Manufacturing of Idaho Facility 2, Preston  
Proposed New Permit to Construct for Public Comment

Dear Mr. Reeder:

The Department of Environmental Quality (DEQ) has prepared a proposed Permit to Construct No.P-2016.0012 for Trails West Manufacturing of Idaho for construction of a new trailer manufacturing facility located at Preston. A public comment period has been requested, and DEQ is scheduling a 30-day public comment period in accordance with IDAPA 58.01.01.209.01.c. Rules for the Control of Air Pollution in Idaho. To find the exact dates and all other information concerning this public comment period please go to our website: <http://www.deq.idaho.gov>

Enclosed is proposed PTC No. P-2016.0012 for your review. You may submit comments during the public comment period if you so choose. Please email them to Name AQ Public Comment@deq.idaho.gov or directly to me at tom.burnham@deq.idaho.gov.

If you have any questions regarding the terms or conditions of the proposed permit, or about the public comment period, please contact me at (208) 373-0502 or tom.burnham@deq.idaho.gov.

Sincerely,

*Tom*

Tom Burnham  
Permit Writer  
Air Quality Division

Permit No. P-2016.0012 PROJ 61687

## Air Quality

### PERMIT TO CONSTRUCT

---

|                          |  |
|--------------------------|--|
| <b>Permittee</b>         | Trails West Manufacturing of Idaho – Industrial Park   |
| <b>Permit Number</b>     | P-2016.0012  |
| <b>Project ID</b>        | 61687  |
| <b>Facility ID</b>       | 041-00022  |
| <b>Facility Location</b> | 950 West Industrial Park Drive<br>Preston, Idaho 83263 |

### Permit Authority

This permit (a) is issued according to the “Rules for the Control of Air Pollution in Idaho” (Rules), IDAPA 58.01.01.200–228; (b) pertains only to emissions of air contaminants regulated by the State of Idaho and to the sources specifically allowed to be constructed or modified by this permit; (c) has been granted on the basis of design information presented with the application; (d) does not affect the title of the premises upon which the equipment is to be located; (e) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (f) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; and (g) in no manner implies or suggests that the Idaho Department of Environmental Quality (DEQ) or its officers, agents, or employees assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment. Changes in design, equipment, or operations may be considered a modification subject to DEQ review in accordance with IDAPA 58.01.01.200–228.

**Date Issued** DRAFT, 2016

---

**Tom Burnham, Permit Writer**

---

**Mike Simon, Stationary Source Manager**

**TABLE OF CONTENTS**

1 Permit Scope ..... 3  
2 TAP & PM Emissions Sources – Including Metal Fabrication & Painting ..... 4  
3 General Provisions ..... 14

# 1 Permit Scope

## Purpose

- 1.1 This is a replacement permit to construct (PTC) a new trailer manufacturing facility.
- 1.2 This PTC replaces the General Automotive Paint permit No. P-2016.0008, issued on May 26, 2016.

## Regulated Sources

- 1.3 Table 1 lists all sources of regulated emissions in this permit.

**Table 1 REGULATED SOURCES**

| Permit Section | Source   | Control Equipment                              |
|----------------|--|--|
| 2              | Spray Painting Operations  | Booths with filters                            |
| 2              | Welding Operations   | Tables located inside the facility with filter |
| 2              | Laser Cutting Operations   | None   |
| 2              | Primer Booth Heater - 1.075 MMBtu/hr<br>Natural Gas Fired        | None   |
| 2              | Paint Booth Heater #1 - 2.0 MMBtu/hr<br>Natural Gas Fired        | None   |
| 2              | Paint Booth Heater #2 - 2.0 MMBtu/hr<br>Natural Gas Fired        | None   |
| 2              | Drying Booth Heater - 1.075 MMBtu/hr<br>Natural Gas Fired        | None   |
| 2              | Curing Booth Heater - 1.075 MMBtu/hr<br>Natural Gas Fired        | None   |
| 2              | Building Heaters (18 units) - 0.15 MMBtu/hr<br>Natural Gas Fired | None   |
| 2              | Building Heaters (4 units) - 0.12 MMBtu/hr<br>Natural Gas Fired  | None   |

## **2 TAP, VOC, & PM Emissions Sources – Including Metal Fabrication & Painting**

### **2.1 Process Description**

Trails West is a manufacturer of horse, stock, and snowmobile trailers. Metal is cut to size on a laser cutting table within the facility. Trailer parts are assembled in the fab shop, sub-assembly, and weld portions of the plant. After assembly the trailers are washed and then primed using an epoxy primer in the prime/cure booth. The trailers are then prepared for painting in the caulking area of the plant. Painting of the trailers is done in a down draft paint booth. After painting the trailers are dried and cured in heated booths. Trailers are then completed in the trim portion of the plant.

### **2.2 Emissions Control Description**

Particulate matter emissions from laser cutting operations are controlled by cutting tables equipped with filters operating inside the facility. Particulate matter emissions from spray painting operations are controlled by conducting operations within booths equipped with filters. Heaters from the prime, paint, dry, and cure booths, building heaters, caulking, and welding activities have no controls.

### **Emission Limits**

#### **2.3 Toxic Air Pollutant (TAP) Limits**

Each calendar day emissions of TAPs from the facility, including but not limited to TAPs emissions from metal fabrication, paints, primers, epoxies, solvents, caulking, welding, laser cutting, and heaters shall not exceed the EL (lb/hr) multiplied by 24 (for TAPs listed in both IDAPA 58.01.01.585 and 586) or the acceptable ambient concentration ( $\text{mg}/\text{m}^3$ ) (for TAPs listed in IDAPA 58.01.01.585) and the acceptable ambient concentration for carcinogens ( $\mu\text{g}/\text{m}^3$ ) (for TAPs listed in IDAPA 58.01.01.586).

#### **2.4 Coating VOC Limit (Reasonable Achievable Control Technology-RACT)**

Coatings including paints, primers, and epoxies shall not contain more than 5.7 pounds VOC per gallon.

#### **2.5 Coating Usage**

The permittee shall not use more than 23,000 gallons of paint in any 12 consecutive calendar months.

### **Operating Requirements**

#### **2.6 Odors**

The permittee shall not allow, suffer, cause, or permit the emission of odorous gases, liquids, or solids into the atmosphere of such nature and duration and under such conditions as would be injurious to human health or welfare, to animal or plant life, or to property, or to interfere unreasonably with the enjoyment of life or property in accordance with IDAPA 58.01.01.776.

#### **2.7 Operating Hours**

Paint, primer, and caulk application operations shall not exceed 2080 hour for any 12 consecutive month period.

## **2.8 Permitted Fuel (RACT)**

The booth and building heating units shall only combust natural gas as fuel.

## **2.9 Spray Gun and Spray Booth Filter System (RACT)**

All coating at this facility shall be conducted within the booth area, with filter system in place, and exhaust fans operating.

- All painting shall be conducted with HVLP spray equipment with minimum 65% transfer efficiency as documented by the spray gun manufacturer.
- The permittee shall install, maintain, and operate according to the manufacturer's specifications and recommendations, a spray booth filter system or a preparation station filter system with a minimum control efficiency of 98% for PM emissions as documented by the filter manufacturer.
- The permittee shall follow the operation and maintenance manual which will include the manufacturers specifications and procedures used to determine when replacement of the filters are required to maintain the 98% efficiency.
- The permittee shall keep a record regarding the when the filters are changed, the frequency of changes, and the method used to determine when the change was necessary.

## **2.10 Laser Cutting Operations**

Laser cutting operations shall be limited to cutting tables equipped with filters located within the facility.

## **Monitoring and Recordkeeping Requirements**

### **2.11 Odor Complaints**

The permittee shall maintain records of all odor complaints received to demonstrate compliance with the Odors Permit Condition. The permittee shall take appropriate corrective action as expeditiously as practicable. The records shall include, at a minimum, the date each complaint was received and a description of the following: the complaint, the permittee's assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.

### **2.12 TAPs Emissions Daily Monitoring Requirements**

Using the material usage records, the permittee shall monitor and record the individual TAP (as listed in IDAPA 58.01.01.585 and 586) emissions from the facility in order to demonstrate compliance with the TAPs emissions limits in Permit Condition 2.3. All emissions calculations shall be maintained on-site in accordance with General Provisions of this permit.

If any of the individual daily TAP emission rate exceeds 24 times the screening emissions level (EL) specified in IDAPA 58.01.01.585 and 586, a modeling analysis shall be conducted to demonstrate compliance with the acceptable ambient concentration ( $\text{mg}/\text{m}^3$ ) (for TAPs listed in IDAPA 58.01.01.585) or the acceptable ambient concentration for carcinogens ( $\mu\text{g}/\text{m}^3$ ) (for TAPs listed in IDAPA 58.01.01.586). Documentation of all calculations and modeling analysis shall be maintained on-site in accordance with General Provisions of this permit

### **2.13 Material Usage Records**

The permittee shall monitor and record daily the usage of all VOC, Solids, and TAP containing materials that emit air pollution including but not limited to welding wire, paints, primers, solvents, caulks, and epoxies. Documentation of all records shall be maintained on-site in accordance with General Provisions of this permit.

## **2.14 Hours of Operations Records**

The permittee shall monitor and record the daily paint, primer, and caulk hours of operation.

## **Reporting Requirements**

**2.15** Each year the permittee shall submit a report by May 1<sup>st</sup> on all TAP modeling analyses that have been conducted during the previous 12 month period. The report shall document the analyses with sufficient detail, including documentation of all calculations and electronic copies of modeling files, so that DEQ can verify the analysis. The report shall be sent to:

DEQ State Office  
Air Quality Division  
1410 N. Hilton  
Boise, ID 83706

The report shall be titled: Trails West Manufacturing Industrial Park– Permit Required Modeling Report.

## **2.16 Excess Emissions**

If a TAP modeling analysis (conducted pursuant to Permit Condition 2.14) shows that emissions of any TAP exceeds the acceptable ambient concentration for any TAP, the permittee shall follow the excess emissions requirements of IDAPA 58.01.01.131 including but not limited to correcting the excess emission condition in accordance with IDAPA 58.01.01.132, and submitting excess emission reports no later than 15 days after the beginning of each such event in accordance with IDAPA 58.01.01.135.

## **40 CFR 63 Subpart HHHHHH Requirements (If Applicable)**

### **2.17 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, General Compliance Requirements**

40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, General Compliance Requirements

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH

- The permittee shall meet the requirements of 40 CFR 63.11173(e)(1). All painters must be certified that they have completed training in the proper spray application of surface coatings and the proper setup and maintenance of spray equipment. The minimum requirements for training and certification are described in 40 CFR 63.11173(f). The spray application of surface coatings is prohibited by persons who are not certified as having completed the training described in 40 CFR 63.11173(f).
- All spray-applied coatings must be applied in a spray booth, preparation station, or mobile enclosure that meets the requirements of 40 CFR 63.11173(e)(2).

- All spray booths, preparation stations, and mobile enclosures must be fitted with a type of filter technology that is demonstrated to achieve at least 98% capture of paint overspray. The procedure used to demonstrate filter efficiency must be consistent with the American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE) Method 52.1.
- Spray booths and preparation stations used to refinish complete motor vehicles or mobile equipment must be fully enclosed with a full roof, and four complete walls or complete side curtains, and must be ventilated at negative pressure so that air is drawn into any openings in the booth walls or preparation station curtains. However, if a spray booth is fully enclosed and has seals on all doors and other openings and has an automatic pressure balancing system, it may be operated at up to, but not more than, 0.05 inches water gauge positive pressure.
- Spray booths and preparation stations that are used to coat miscellaneous parts and products or vehicle subassemblies must have a full roof, at least three complete walls or complete side curtains, and must be ventilated so that air is drawn into the booth. The walls and roof of a booth may have openings, if needed, to allow for conveyors and parts to pass through the booth during the coating process.
- All spray-applied coatings must be applied with a high volume, low pressure (HVLP) spray gun, electrostatic application, airless spray gun, or air-assisted airless spray gun, in accordance with 40 CFR 63.11173(e)(3).
- All paint spray gun cleaning must be done so that an atomized mist or spray of gun cleaning solvent and paint residue is not created outside of a container that collects used gun cleaning solvent, in accordance with 40 CFR 63.11173(e)(4). Spray gun cleaning may be done by using a fully enclosed spray gun washer.
- Each owner or operator must ensure and certify that all new and existing personnel, including contract personnel, who spray apply surface coatings, as defined in 40 CFR 63.11180, are trained in the proper application of surface coatings as required by 40 CFR 63.11173(e)(1), in accordance with 40 CFR 63.11173(f). The training program must include, at a minimum:
  - A list of all current personnel by name and job description who are required to be trained;
  - Hands-on and classroom instruction that addresses, at a minimum, initial and refresher training in the following topics:
    - Spray gun equipment selection, set up, and operation, including measuring coating viscosity, selecting the proper fluid tip or nozzle, and achieving the proper spray pattern, air pressure and volume, and fluid delivery rate;
    - Spray technique for different types of coatings to improve transfer efficiency and minimize coating usage and overspray, including maintaining the correct spray gun distance and angle to the part, using proper banding and overlap, and reducing lead and lag spraying at the beginning and end of each stroke;
    - Routine spray booth and filter maintenance, including filter selection and installation; and
    - Environmental compliance with the requirements of 40 CFR 63, Subpart HHHHHH.
- A description of the methods to be used at the completion of initial or refresher training to demonstrate, document, and provide certification of successful completion of the required training. Owners and operators who can show by documentation or certification that a painter's work experience and/or training has resulted in training equivalent to the training required are not required to provide the initial training to these painters.

- All new and existing personnel at the facility, including contract personnel, who spray apply surface coatings, as defined in 40 CFR 63.11180, must be trained by the dates specified in 40 CFR 63.11173(g). Employees who transfer within a company to a position as a painter are subject to the same requirements as a new hire.
  - All personnel must be trained and certified no later than 180 days after hiring or no later than January 10, 2011, whichever is later. Painter training that was completed within five years prior to the date training is required, and that meets the requirements specified in 40 CFR 63.11173(f)(2) of this section satisfies this requirement and is valid for a period not to exceed five years after the date the training is completed.
  - Training and certification will be valid for a period not to exceed five years after the date the training is completed, and all personnel must receive refresher training that meets the requirements of this section and be re-certified every five years.
- The parts of the General Provisions which apply to the permittee are specified in Table 4, in accordance with 40 CFR 63.11174(a).

**Table 2 APPLICABILITY OF GENERAL PROVISIONS TO SUBPART HHHHHH OF PART 63**

| <b>Citation</b>         | <b>Subject</b>   | <b>Explanation</b>   |
|-------------------------|--|--|
| 40 CFR 63.1(a)(1)-(12)  | General Applicability  |  |
| 40 CFR 63.1(b)(1)-(3)   | Initial Applicability Determination  | Applicability of subpart HHHHHH is also specified in 40 CFR 63.11170.  |
| 40 CFR 63.1(c)(1)       | Applicability After Standard Established                                   |  |
| 40 CFR 63.1(c)(2)       | Applicability of Permit Program for Area Sources                           |  |
| 40 CFR 63.1(c)(5)       | Notifications  |  |
| 40 CFR 63.2             | Definitions  | Additional definitions are specified in 40 CFR 63.11180.   |
| 40 CFR 63.3(a)-(c)      | Units and Abbreviations  |  |
| 40 CFR 63.4(a)(1)-(5)   | Prohibited Activities  |  |
| 40 CFR 63.4(b)-(c)      | Circumvention/Fragmentation  |  |
| 40 CFR 63.6(a)          | Compliance With Standards and Maintenance Requirements—Applicability       |  |
| 40 CFR 63.6(b)(1)-(7)   | Compliance Dates for New and Reconstructed Sources                         | 40 CFR 63.11172 specifies the compliance dates.  |
| 40 CFR 63.6(c)(1)-(5)   | Compliance Dates for Existing Sources                                      | 40 CFR 63.11172 specifies the compliance dates.  |
| 40 CFR 63.6(e)(1)-(2)   | Operation and Maintenance  |  |
| 40 CFR 63.6(f)(1)       | Compliance Except During Startup, Shutdown, and Malfunction                |  |
| 40 CFR 63.6(f)(2)-(3)   | Methods for Determining Compliance   |  |
| 40 CFR 63.6(g)(1)-(3)   | Use of an Alternative Standard   |  |
| 40 CFR 63.6(i)(1)-(16)  | Extension of Compliance  |  |
| 40 CFR 63.6(j)          | Presidential Compliance Exemption  |  |
| 40 CFR 63.9(a)-(d)      | Notification Requirements  | 40 CFR 63.11175 specifies notification requirements.   |
| 40 CFR 63.9(i)          | Adjustment of Submittal Deadlines  |  |
| 40 CFR 63.9(j)          | Change in Previous Information   | 40 CFR 63.11176(a) specifies the dates for submitting the notification of changes report.  |
| 40 CFR 63.10(a)         | Recordkeeping/Reporting—Applicability and General Information              |  |
| 40 CFR 63.10(b)(1)      | General Recordkeeping Requirements   | Additional requirements are specified in 40 CFR 63.11177.  |
| 40 CFR 63.10(b)(2)(xii) | Waiver of recordkeeping requirements                                       |  |
| 40 CFR 63.10(b)(2)(xiv) | Records supporting notifications   |  |
| 40 CFR 63.10(b)(3)      | Recordkeeping Requirements for Applicability Determinations                |  |
| 40 CFR 63.10(d)(1)      | General Reporting Requirements   | Additional requirements are specified in 40 CFR 63.11176.  |
| 40 CFR 63.10(d)(4)      | Progress Reports for Sources With Compliance Extensions                    |  |
| 40 CFR 63.10(f)         | Recordkeeping/Reporting Waiver   |  |
| 40 CFR 63.12            | State Authority and Delegations  |  |
| 40 CFR 63.13            | Addresses of State Air Pollution Control Agencies and EPA Regional Offices |  |
| 40 CFR 63.14            | Incorporation by Reference   | Test methods for measuring paint booth filter efficiency and spray gun transfer efficiency in 40 CFR 63.11173(e)(2) and (3) are incorporated and included in 40 CFR 63.14. |
| 40 CFR 63.15            | Availability of Information/Confidentiality                                |  |
| 40 CFR 63.16(a)         | Performance Track Provisions—reduced reporting                             |  |

**2.18 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Recordkeeping**

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- The permittee shall keep the following records in accordance with 40 CFR 63.11177(a) through (d) and (h).
  - Certification that each painter has completed the training specified in 40 CFR 63.11173(f) with the date the initial training and the most recent refresher training was completed.
  - Documentation of the filter efficiency of any spray booth exhaust filter material, according to the procedure in 40 CFR 63.11173(e)(2).
  - Copies of any notification submitted as required by 40 CFR 63.11175 and copies of any report submitted as required by 40 CFR 63.11176.
  - Records of any deviation from the requirements in 40 CFR 63.11173, 63.11174, 63.11175, or 63.11176. These records must include the date and time period of the deviation, and a description of the nature of the deviation and the actions taken to correct the deviation.
  - Records of any assessments of source compliance performed in support of the initial notification, notification of compliance status, or annual notification of changes report.
- The permittee shall maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record in accordance with 40 CFR 63.11178(a). Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period.
- In accordance with 40 CFR 63.11178(a), the permittee shall maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record. Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period.

**2.19 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Notifications**

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- *Initial Notification.* The permittee must submit the initial notification required by 40 CFR 63.9(b) in accordance with 40 CFR 63.11175(a). For this existing source, the permittee must submit the Initial Notification no later than January 11, 2010. The initial notification must provide the following information.

- The company name, if applicable;
  - The name, title, street address, telephone number, e-mail address (if available), and signature of the owner and operator, or other certifying company official;
  - The street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
  - An identification of the relevant standard, such as 40 CFR part 63, Subpart HHHHHH;
  - A brief description of the type of operation. For all surface coating operations, indicate whether the source is a motor vehicle and mobile equipment surface coating operation or a miscellaneous surface coating operation, and include the number of spray booths and preparation stations, and the number of painters usually employed at the operation.
  - A statement of whether the source is already in compliance with each of the relevant requirements of this subpart, or whether the source will be brought into compliance by the compliance date.
  - The permittee must certify in the initial notification whether the source is in compliance with each of the requirements of 40 CFR 63, Subpart HHHHHH. If the permittee is certifying in the initial notification that the source is in compliance with the relevant requirements of this subpart, then include also a statement by a responsible official with that official's name, title, phone number, e-mail address (if available) and signature, certifying the truth, accuracy, and completeness of the notification, a statement that the source has complied with all the relevant standards of this subpart, and that this initial notification also serves as the notification of compliance status.
- *Notification of Compliance Status.* The permittee is not required to submit a separate notification of compliance status in addition to the initial notification provided the permittee was able to certify compliance on the date of the initial notification as part of the initial notification, and the permittee's compliance status has not since changed in accordance with 40 CFR 63.11175(b). The permittee must submit a Notification of Compliance Status by March 11, 2011. The permittee is required to submit the following information with the Notification of Compliance Status:
    - The company's name and the street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
    - The name, title, address, telephone, e-mail address (if available) and signature of the owner and operator, or other certifying company official, certifying the truth, accuracy, and completeness of the notification and a statement of whether the source has complied with all the relevant standards and other requirements of this subpart or an explanation of any noncompliance and a description of corrective actions being taken to achieve compliance. For surface coating operations, the relevant requirements are specified in 40 CFR 63.11173(e) through (g).
    - The date of the Notification of Compliance Status.

**2.20 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Reports**

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- Annual Notification of Changes Report. In accordance with 40 CFR 63.11176, the permittee is required to submit a report in each calendar year in which information previously submitted in either the initial notification required by 40 CFR 63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted has changed. Deviations from the relevant requirements in 40 CFR 63.11173(a) through (d) or 40 CFR 63.11173(e) through (g) on the date of the report will be deemed to be a change. The annual notification of changes report must be submitted prior to March 1 of each calendar year when reportable changes have occurred and must include the following information.
  - The company's name and the street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
  - The name, title, address, telephone, e-mail address (if available) and signature of the owner and operator, or other certifying company official, certifying the truth, accuracy, and completeness of the notification and a statement of whether the source has complied with all the relevant standards and other requirements of this subpart or an explanation of any noncompliance and a description of corrective actions being taken to achieve compliance.
- Any notifications or reporting required by the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH or Subpart A – General Provisions shall be submitted to both of the following addresses in accordance with 40 CFR 63.13:

EPA Region 10  
Manager, Federal and Delegated Air Programs Unit  
Office of Air, Waste, and Toxics  
1200 Sixth Avenue, Suite 900  
(AWT-107)  
Seattle, WA 98101

And,

Air Quality Permit Compliance  
Department of Environmental Quality  
Pocatello Regional Office  
444 Hospital Way, #300  
Pocatello, ID 83201

Phone: (208) 236-6160  
Fax: (208) 236-6168

## **2.21 Incorporation of Federal Requirements by Reference**

Unless expressly provided otherwise, any reference in this permit to any document identified in IDAPA 58.01.01.107.03 shall constitute the full incorporation into this permit of that document for the purposes of the reference, including any notes and appendices therein. Documents include, but are not limited to:

- National Emission Standards for Hazardous Air Pollutants (NESHAP) Area Sources, 40 CFR Part 63, Subpart HHHHHH.

For permit conditions referencing or cited in accordance with any document incorporated by reference (including permit conditions identified as NESHAP), should there be any conflict between the requirements of the permit condition and the requirements of the document, the requirements of the document shall govern, including any amendments to that regulation.

## 3 General Provisions

### General Compliance

3.1 The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the Rules for the Control of Air Pollution in Idaho. The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit and the Rules for the Control of Air Pollution in Idaho, and the Environmental Protection and Health Act, Idaho Code §39-101, et seq.

**[Idaho Code §39-101, et seq.]**

3.2 The permittee shall at all times (except as provided in the Rules for the Control of Air Pollution in Idaho) maintain in good working order and operate as efficiently as practicable, all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.

**[IDAPA 58.01.01.211, 5/1/94]**

3.3 Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules and regulations.

**[IDAPA 58.01.01.212.01, 5/1/94]**

### Inspection and Entry

3.4 Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:

- Enter upon the permittee's premises where an emissions source is located or emissions related activity is conducted, or where records are kept under conditions of this permit;
- Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
- Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
- As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

**[Idaho Code §39-108]**

## Performance Testing

- 3.5** If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ, at its option, may have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.
- 3.6** All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.
- 3.7** Within 60 days, following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The written report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00]

## Monitoring and Recordkeeping

- 3.8** The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Records of monitoring information shall include, but not be limited to the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

## Excess Emissions

- 3.9** The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions due to startup, shutdown, scheduled maintenance, safety measures, upsets and breakdowns.

[IDAPA 58.01.01.130-136, 4/5/00]

## Certification

- 3.10** All documents submitted to DEQ, including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

### **False Statements**

- 3.11** No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit, or any applicable rule or order in force pursuant thereto.  
**[IDAPA 58.01.01.125, 3/23/98]**

### **Tampering**

- 3.12** No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.  
**[IDAPA 58.01.01.126, 3/23/98]**

### **Transferability**

- 3.13** This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.  
**[IDAPA 58.01.01.209.06, 4/11/06]**

### **Severability**

- 3.14** The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.  
**[IDAPA 58.01.01.211, 5/1/94]**