



STATE OF IDAHO
DEPARTMENT OF
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, Idaho 83706 • (208) 373-0502

C.L. "Butch" Otter, Governor
Toni Hardesty, Director

June 22, 2010

Gary Multanen, President
Best Bath Systems, Inc.
4545 Enterprise Street
Boise, Idaho 83705

RE: Facility ID No. 027-00103, Best Bath Systems, Inc., Caldwell
Final Permit Letter, Permit to Construct No. P-2010.0047

Dear Mr. Multanen:

The Department of Environmental Quality (DEQ) is issuing Permit to Construct (PTC) No. P-2010.0047 to Best Bath Systems, Inc. for the construction of a new fiberglass tub and shower unit manufacturing facility in Caldwell, ID, in accordance with IDAPA 58.01.01.200 through 228 (Rules for the Control of Air Pollution in Idaho). This permit is based on your permit application received on March 29, 2010. This permit is effective immediately. This permit does not release Best Bath Systems, Inc. from compliance with all other applicable federal, state, or local laws, regulations, permits, or ordinances.

In accordance with IDAPA 58.01.01.313.01.b, you shall submit a complete application to DEQ for an initial Tier I operating permit within 12 months of becoming a Tier I source or commencing operation.

Pursuant to the Construction and Operation Notification General Provision of your permit, it is required that construction and operation notification be provided. Please provide this information as listed to DEQ at the following Regional Office:

Air Quality Permit Compliance
Department of Environmental Quality
Boise Regional Office
1445 N. Orchard
Boise, ID 83706
Phone: (208) 373-0550 Fax: (208) 373-0287

In order to fully understand the compliance requirements of this permit, DEQ highly recommends that you schedule a meeting with J. R. Fuentes, Title V and Area Source Specialist, at (208) 373-0550 to review and discuss the terms and conditions of this permit. Should you choose to schedule this meeting, DEQ recommends that the following representatives attend the meeting: your facility's plant manager, responsible official, environmental contact, and any other staff responsible for day-to-day compliance with permit conditions.

Pursuant to IDAPA 58.01.23, you, as well as any other entity, may have the right to appeal this final agency action within 35 days of the date of this decision. However, prior to filing a petition for a contested case, I encourage you to contact Ken Hanna at (208) 373-0502 or kenneth.hanna@deq.idaho.gov to address any questions or concerns you may have with the enclosed permit.

Sincerely,


A handwritten signature in black ink that reads "Mike Simon". The signature is written in a cursive, flowing style.

Mike Simon
Stationary Source Program Manager
Air Quality Division

MS/KH

Project No. P-2010.0047

Enclosures

| | | | |
|--|-----------------------|-----------------------------|---------------|
| <p style="text-align: center;">Air Quality PERMIT TO CONSTRUCT State of Idaho Department of Environmental Quality</p> | PERMIT NUMBER | CLASS | SIC |
| | P-2010.0047 | A | 3088 |
| | FACILITY ID | AQCR | NAICS |
| | 027-00103 | 64 | 326191 |
| | ZONE | UTM COORDINATES (km) | |
| | 11 | 523.5 | 4834.7 |
| PERMITTEE | | | |
| Best Bath Systems, Inc. | | | |
| PROJECT | | | |
| Initial Permit to Construct for a New Fiberglass Manufacturing Facility | | | |
| MAILING ADDRESS | CITY | STATE | ZIP |
| 723 Garber Street | Caldwell | ID | 83605 |
| FACILITY CONTACT | TITLE | TELEPHONE | |
| Merrill Balius | Environmental Manager | (208) 955-7377 | |
| RESPONSIBLE | TITLE | TELEPHONE | |
| Gary Multanen | President | (208) 342-6823 | |
| EXACT PLANT LOCATION | | COUNTY | |
| 723 Garber Street; Caldwell, ID | | Canyon | |
| GENERAL NATURE OF BUSINESS & KINDS OF PRODUCTS | | | |
| Manufacturing of fiberglass tub and shower units | | | |
| PERMIT AUTHORITY | | | |
| <p>This permit is issued according to the Rules for the Control of Air Pollution in Idaho, IDAPA 58.01.01.200 through 228, and pertains only to emissions of air contaminants regulated by the state of Idaho and to the sources specifically allowed to be constructed or modified by this permit.</p> <p>This permit (a) does not affect the title of the premises upon which the equipment is to be located; (b) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (c) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; (d) in no manner implies or suggests that the Department of Environmental Quality (DEQ) or its officers, agents, or employees, assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment.</p> <p>This permit will expire if construction has not begun within two years of its issue date or if construction is suspended for one year.</p> <p>This permit has been granted on the basis of design information presented with its application. Changes in design, equipment or operations may be considered a modification. Modifications are subject to DEQ review in accordance with IDAPA 58.01.01.200 through 228 of the Rules for the Control of Air Pollution in Idaho.</p> | | | |
|  | | DATE ISSUED | June 22, 2010 |
| KEN HANNA, PERMIT WRITER | | | |
|  | | | |
| MIKE SIMON, STATIONARY SOURCE MANAGER | | | |

PERMIT TO CONSTRUCT SCOPE 3
PRODUCTION OF BATH UNITS (STACKS EF-9, EF-10, EF-11, EF-12 AND EF-14)..... 4
PERMIT TO CONSTRUCT GENERAL PROVISIONS..... 9

PERMIT TO CONSTRUCT SCOPE

Purpose

1. This is the initial permit to construct a manufacturing facility for fiberglass tub and shower units.
2. The emission sources regulated by this permit are listed in the following table.

Table 1 REGULATED SOURCES

| Source Descriptions | Emission Controls |
|--|--|
| Coatings applications during fabrication of fiberglass reinforced plastics. Emissions from application process exhaust to Stacks EF-9, EF-10, EF-11, EF-12 and EF-14. | For PM/PM ₁₀ /PM _{2.5} control: 1-inch fiberglass filter (approximately 72% efficiency); and fiberglass bulk media filter (approximately 84% efficiency) For VOC and HAP control: Control of operations in accordance with NESHAP/MACT requirements |
| Combustion emissions from building unit heaters that are vented thru the roof. There are 11 small gas-fired units installed throughout the facility with a typical design input of 0.30 MMBtu/hr. | Use of natural gas fuel, and good combustion control |
| Combustion emissions from two makeup air units with a combined input rating of approximately 9.6 MMBtu/hr. Emissions from these direct-fired natural gas fueled units are vented thru the fiberglass production area exhaust stacks. | Use of natural gas fuel, and good combustion control |

PRODUCTION OF BATH UNITS (STACKS EF-9, EF-10, EF-11, EF-12 AND EF-14)

Process Description

3. Best Bath Systems produces fiberglass shower and tub units primarily using spray layup techniques on open molds. Typically, three polyester-styrene layers are applied to molds to create the units: gel coat, barrier coat, and glass-reinforced resin. A fourth polymeric diisocyanate material, "blue foam," is sprayed on to create reinforced floors. The first three layers are applied in the Lamination Area. Accents may be applied in a paint booth (EF-14).
4. The air ventilation system for production operations exhausts through a series of two filters to stacks as listed below. The exhaust from the air ventilation system first passes through a fiberglass bulk media filter and then through a 1-inch fiberglass filter. Emissions from the makeup air units are co-mingled with the production area emissions, and exit the building through the production area stacks.

Table 2 PRODUCTION AREA EMISSIONS UNIT DESCRIPTION

| Emissions Units / Processes | Emission Control Devices | Emission Points |
|--|--|-------------------------------------|
| Coatings applications during fabrication of fiberglass reinforced plastics. | For PM/PM ₁₀ /PM _{2.5} control: 1-inch fiberglass filter (approximately 72% efficiency); and fiberglass bulk media filter (approximately 84% efficiency) | Stacks EF-9, EF-10, EF-11 and EF-12 |
| Accent application in a paint booth | For VOC and HAP control: Control of operations in accordance with NESHAP/MACT requirements | Stack EF-14 |
| Trim and finish operations. Rough edges are trimmed and plumbing holes are drilled. Exhaust from this area is filtered and exhausted back into the Trim Room work area. It is not directly vented to the outside. | For PM/PM ₁₀ /PM _{2.5} control: High-efficiency cartridge filters with a minimum efficiency of 90%. | --- |
| Combustion emissions from building unit heaters that are vented thru the roof. There are 11 small gas-fired units installed throughout the facility with a typical design input of 0.30 MMBtu/hr. | Use of natural gas fuel, and good combustion control | Each unit heater has its own stack |
| Combustion emissions from two makeup air units with a combined input rating of approximately 9.6 MMBtu/hr. Emissions from these direct-fired natural gas fueled units are vented thru the fiberglass production area exhaust stacks. | Use of natural gas fuel, and good combustion control | Stacks EF-9, EF-10, EF-11 and EF-12 |

Limitations

5. Emissions Limits

Total emissions of particulate matter with an aerodynamic diameter less than or equal to a nominal 10 micrometers (PM₁₀) from Stacks EF-9, EF-10, EF-11, and EF-12 shall not exceed any corresponding emission limit listed in Table 3 and Permit Condition 6. Total emissions of volatile organic compounds (VOCs) from Stacks EF-9, EF-10, EF-11, and EF-12 shall not exceed any corresponding emission limit listed in Table 3. Three years from the date of notification of exceedance of the HAP emission threshold specified in 40 CFR 63.5805(c), the total VOC emission limit specified in Table 3 of this permit shall not apply, and the permittee shall comply with the emission limits specified in Permit Condition 6.

Table 3 LAMINATION AREA AND BLUE BOTTOM AREA EMISSION LIMITS^a

| Pollutant | lb/hr ^c | T/yr ^d |
|-------------------------------|--------------------|-------------------|
| PM ₁₀ ^b | 1.60 | |
| Total VOCs | | 108 |

- a) In absence of any other credible evidence, compliance is assured by complying with permit operating, monitoring, and record keeping requirements.
- b) Particulate matter with an aerodynamic diameter less than or equal to a nominal ten (10) micrometers, including condensable particulate as defined in IDAPA 58.01.01.006.81.
- c) Pounds per hour, as determined by a test method prescribed by IDAPA 58.01.01.157, EPA reference method, or DEQ-approved alternative.
- d) Tons per any consecutive 12-calendar month period.

6. MACT Limitations, Work Practice Standards, & Compliance Deadlines

On and after the compliance date specified in 40 CFR 63.5800 and 40 CFR 63, Subpart WWWW, Table 2, the permittee shall comply with the applicable emission limitations, operating limitations and work practice standard of the National Emissions Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production, 40 CFR 63, Subpart WWWW. Please refer to the following sections of the rule:

- Emission Limitations: 40 CFR 63.5805; 40 CFR 63, Subpart WWWW, Table 3, 40 CFR 63; Subpart WWWW, Table 5; and
- Work Practice Standards: 40 CFR 63.5805; 40 CFR 63, Subpart WWWW, Table 4.

7. Opacity Limit

Emissions from Stacks EF-9, EF-10, EF-11, EF-12, or EF-14, or any other stack, vent, or functionally equivalent opening associated with the coating application process, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

8. Reasonable Control of Fugitive Dust Emissions

In accordance with IDAPA 58.01.01.651, all reasonable precautions shall be taken to prevent PM from becoming airborne. In determining what is reasonable, considerations will be given to factors such as the proximity of dust-emitting operations to human habitations and/or activities and atmospheric conditions that might affect the movement of PM. Some of the reasonable precautions include, but are not limited to, the following:

- Use, where practical, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads, or the clearing of lands.
- Application, where practical, of asphalt, water or suitable chemicals to, or covering of dirt roads, material stockpiles, and other surfaces which can create dust.

- Installation and use, where practical, of hoods, fans, and fabric filters or equivalent systems to enclose and vent the handling of dusty materials. Adequate containment methods should be employed during sandblasting or other operations.
- Covering, where practical, of open-bodied trucks transporting materials likely to give rise to airborne dusts.
- Paving of roadways and their maintenance in a clean condition, where practical.
- Prompt removal of earth or other stored material from streets, where practical.

9. Odorous Emissions

Odorous gases shall not be emitted to the atmosphere in such quantities as to cause air pollution, as required by IDAPA 58.01.01.775.

10. Use of Natural Gas in Fuel-burning Equipment

The permittee shall burn natural gas exclusively in the fuel-burning equipment at this facility.

Compliance Demonstration Requirements

11. Spray Gun and Filter Specifications

- Low-pressure spray guns shall be used for gel-coat applications. The facility shall use Magnum Venus model ATG-3500 or functionally equivalent spray guns demonstrated to produce similar operating pressures and emissions.
- Air ventilation system for spray operations shall be equipped with a 1-inch fiberglass filter and then through a fiberglass bulk media filter with a combined collection efficiency of at least 90% for PM₁₀, or filters with an equivalent or greater collection efficiency. The combined efficiency may be determined using the following equation:

$$\text{Combined collection efficiency} = E = 1 - [(1-e_1) * (1-e_2)]$$

Where: e_1 = PM₁₀ collection efficiency for the initial filter; and
 e_2 = PM₁₀ collection efficiency for the secondary filter (e.g., where 72% collection efficiency is expressed as 0.72)

12. MACT Compliance Demonstration Requirements

On and after the compliance date specified in 40 CFR 63.5800 and 40 CFR 63, Subpart WWWW, Table 2, the permittee shall comply with the applicable compliance demonstration requirements of the National Emissions Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production, 40 CFR 63, Subpart WWWW. Please refer to the following sections of the rule

- Options For Meeting The Standards For Open Molding And Centrifugal Casting Operations At New And Existing Sources: 40 CFR 63.5810;
- General Compliance Requirements: 40 CFR 63.5835;
- Performance Test Or Other Initial Compliance Demonstration: 40 CFR 63.5840, 40 CFR 63.5860;
- Continuous Compliance Demonstration: 40 CFR 63.5895, 40 CFR 63.5900; and
- Recordkeeping: 40 CFR 63.5905, 40 CFR 63.5910, 40 CFR 63.5915, 40 CFR 63.5920;
- General Provisions: 40 CFR 63.5925 and 40 CFR 63, Subpart WWWW, Table 15.

13. Material Usage Records

The permittee shall maintain records that contain, but are not limited to, the following information:

- the name and identification number for each gel-coat, resin, adhesive, catalyst, paint, promoter, styrene, and wax used;
- the percent by weight of each VOC in each compound;
- gallons and pounds of gel-coat, resin, adhesive, catalyst, paint, promoter, styrene, and wax used per month; and

14. VOC Emissions Determination Equation

The permittee shall calculate and record on a monthly basis the annual VOC emission rate expressed as tons per any consecutive 12-month period, from the facility to demonstrate compliance with the annual VOC emission limit in Table 3 of Permit Condition 5.

15. Operations and Maintenance Manual for Dust Collection System

Within 60 days of issuance of this permit, the permittee shall have developed an Operations and Maintenance (O&M) Manual for the dust collection system. The manual will describe procedures that will be followed to comply with General Provision 24 and the manufacturer specifications for the dust filter system. The manual shall include, but not be limited to, the following provisions:

- Inspect the filters weekly for collapse, and record date of inspection.
- Replace filters when collapsed or otherwise not functioning properly.
- Maintain negative air pressure inside the building.

16. Odor Management Plan

Within 60 days of issuance of this permit, the permittee shall have developed an Odor Management Plan for the facility. The plan shall describe procedures that will be followed to comply with Permit Condition 9. The plan shall include, but not be limited to, the following provisions:

- Maintain negative air pressure inside the building.
- Keep all storage containers and vessels closed when not in use.
- Keep the door to the mixing tank room closed while extenders and fillers are being added to the resin matrix.
- Maintain records of all odor complaints received.
- Take appropriate corrective action as expeditiously as practicable on all complaints of merit.
- Maintain records of the permittee's assessment of the validity of complaints received.
- Maintain records of any corrective action taken, and the date the corrective action was taken.

17. Particulate Matter Performance Test

Within 60 days after achieving the maximum production rate at which the source will operate, but not later than 180 days after initial start-up, the permittee shall conduct a performance test to measure PM₁₀ emissions from Stacks EF-9 and EF-10. The performance test, and any subsequent performance tests conducted to demonstrate compliance, shall be performed in accordance with IDAPA 58.01.01.157, General Provisions 28 - 30, and the following requirements:

- Visible emissions shall be observed during each performance test run using the methods specified in IDAPA 58.01.01.625.
- For each stack, the maximum number of spray areas attached to that stack shall be in operation during the performance test run. The number and type of spray guns in operation shall be recorded, as shall the materials used and throughput in pounds per hour (lb/hr).
- The permittee shall record the fuel-burning equipment in operation during the performance test that exhausts to Stacks EF-9 and EF-10, if any.

18. Visible Emissions Monitoring

The permittee shall conduct a quarterly (by calendar) facility-wide inspection of potential point sources (i.e., each stack, vent or functionally equivalent opening) of visible emissions during daylight hours and under normal operating conditions. There shall be a minimum of at least 60 days between each inspection. Unless visible emissions are present, no formal Method 9 visible emissions observation is required. If any visible emissions are present from any point of emission, the permittee shall either take corrective action within 24 hours to remedy the cause of the visible emissions, or conduct a Method 9 evaluation of the emissions using the procedures in IDAPA 58.01.01.625. If the corrective action does not eliminate the visible emissions, then a Method 9 visible emission observation shall be required.

If opacity is greater than 20% for a period or periods aggregating more than three minutes in any 60-minute period, the permittee shall take all necessary corrective action and report the exceedance.

The permittee shall maintain records of the results of each visible emission inspection. The records shall, at a minimum, include the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time of each inspection, the permittee's assessment of the conditions existing at the time visible emissions are present (if observed), and any corrective action taken. Records shall be maintained in accordance with General Provision 31.

19. Fugitive Dust Monitoring

The permittee shall conduct quarterly (by calendar) facility-wide inspections of potential sources of fugitive dust emissions, during daylight hours and under normal operating conditions, to ensure that the methods used to reasonably control fugitive dust emissions are effective. If fugitive dust emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive dust emission inspection. The records shall, at a minimum, include the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive dust emissions were present (if observed), any corrective action taken, and the date the corrective action was taken. The most recent five years of records shall be kept onsite and shall be made available to DEQ representatives upon request. Records shall be maintained in accordance with General Provision 31.

Reporting Requirements

20. Operations & Maintenance Manual and Odor Management Plan

Within 60 days of issuance of this permit, the permittee shall submit to DEQ, for approval, the O&M Manual and Odor Management Plan required in Permit Conditions 15 and 16, respectively.

21. Permit Application Requirements

In accordance with IDAPA 58.01.01.313.01.b, the permittee shall submit a complete application to DEQ for an initial Tier I operating permit within 12 months of becoming a Tier I source or commencing operation.

22. MACT Notifications And Reporting Requirements

On and after the compliance date specified in 40 CFR 63.5800 and 40 CFR 63, Subpart WWWW, Table 2, the permittee shall comply with the applicable notifications and reporting requirements of the National Emissions Standards for Hazardous Air Pollutants: Reinforced Plastic Composites Production, 40 CFR 63, Subpart WWWW. Please refer to the following sections of the rule:

- Notifications: 40 CFR 63.5905; 40 CFR 63, Table 13;
- Initial Compliance Report: 40 CFR 63.5840; 40 CFR 63.5860; 40 CFR 63.5910; and
- Semiannual Report: 40 CFR 63.5910.

PERMIT TO CONSTRUCT GENERAL PROVISIONS

General Compliance

23. The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the Rules for the Control of Air Pollution in Idaho. The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit and the Rules for the Control of Air Pollution in Idaho, and the Environmental Protection and Health Act, Idaho Code §39-101, et seq.
- [Idaho Code §39-101, et seq.]**
24. The permittee shall at all times (except as provided in the Rules for the Control of Air Pollution in Idaho) maintain in good working order and operate as efficiently as practicable, all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.
- [IDAPA 58.01.01.211, 5/1/94]**
25. Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules and regulations.
- [IDAPA 58.01.01.212.01, 5/1/94]**

Inspection and Entry

26. Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:
- Enter upon the permittee's premises where an emissions source is located or emissions related activity is conducted, or where records are kept under conditions of this permit;
 - Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
 - Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
 - As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

[Idaho Code §39-108]

Construction and Operation Notification

27. The permittee shall furnish DEQ written notifications as follows in accordance with IDAPA 58.01.01.211:
- A notification of the date of initiation of construction, within five working days after occurrence;
 - A notification of the date of any suspension of construction, if such suspension lasts for one year or more;
 - A notification of the anticipated date of initial start-up of the stationary source or facility not more than sixty days or less than thirty days prior to such date;
 - A notification of the actual date of initial start-up of the stationary source or facility within fifteen days after such date; and

- A notification of the initial date of achieving the maximum production rate, within five working days after occurrence - production rate and date.

[IDAPA 58.01.01.211, 5/1/94]

Performance Testing

28. If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ, at its option, may have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.
29. All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.
30. Within 30 days following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The written report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00]

Monitoring and Recordkeeping

31. The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Records of monitoring information shall include, but not be limited to the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

Excess Emissions

32. The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions due to startup, shutdown, scheduled maintenance, safety measures, upsets and breakdowns.

[IDAPA 58.01.01.130-136, 4/5/00]

Certification

33. All documents submitted to DEQ, including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

False Statements

34. No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit, or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.125, 3/23/98]

Tampering

35. No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.126, 3/23/98]

Transferability

36. This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.
[IDAPA 58.01.01.209.06, 4/11/06]

Severability

37. The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.
[IDAPA 58.01.01.211, 5/1/94]