


<p style="text-align: center;">Air Quality PERMIT TO CONSTRUCT State of Idaho Department of Environmental Quality</p>		PERMIT NUMBER	CLASS	SIC
		P-2009.0095	B	3715
		FACILITY ID	AQCR	NAICS
		083-00068	63	336214
		ZONE	UTM COORDINATES (km)	
11	706.2	4713.8		
PERMITTEE				
Charmac Trailers				
PROJECT				
PTC Permit				
MAILING ADDRESS	CITY	STATE	ZIP	
P.O. Box 205	Twin Falls	ID	83303	
FACILITY CONTACT	TITLE	TELEPHONE		
Lloyd Casperson	President	(208) 733-5241		
RESPONSIBLE	TITLE	TELEPHONE		
Lloyd Casperson	President	(208) 733-5241		
EXACT PLANT LOCATION		COUNTY		
425 S. Park Avenue West, Twin Falls		Twin Falls		
GENERAL NATURE OF BUSINESS & KINDS OF PRODUCTS				
Recreational and transport trailer manufacturing and painting facility				
PERMIT AUTHORITY				
<p>This permit is issued according to the Rules for the Control of Air Pollution in Idaho, IDAPA 58.01.01.200 through 228, and pertains only to emissions of air contaminants regulated by the state of Idaho and to the sources specifically allowed to be constructed or modified by this permit.</p> <p>This permit (a) does not affect the title of the premises upon which the equipment is to be located; (b) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (c) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; (d) in no manner implies or suggests that the Department of Environmental Quality (DEQ) or its officers, agents, or employees, assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment.</p> <p>This permit will expire if construction has not begun within two years of its issue date or if construction is suspended for one year.</p> <p>This permit has been granted on the basis of design information presented with its application. Changes in design, equipment or operations may be considered a modification. Modifications are subject to DEQ review in accordance with IDAPA 58.01.01.200 through 228 of the Rules for the Control of Air Pollution in Idaho.</p>				
		DATE ISSUED	January 6, 2010	
DARRIN PAMPALAN, P.E., PERMIT WRITER				
				
MIKE SIMON, STATIONARY SOURCE MANAGER				

PERMIT TO CONSTRUCT SCOPE3
PAINT BOOTHS NO. 1 AND 24
PERMIT TO CONSTRUCT GENERAL PROVISIONS16

PERMIT TO CONSTRUCT SCOPE

Purpose

1. This is a modification of a Tier II permit and modifies the permit as follows. This permit allows the facility additional flexibility by removing daily and annual coating use limits. Instead, the permit requires additional monitoring and recordkeeping requirements to demonstrate compliance with the PM₁₀, VOC, HAPs, and TAPs emissions limits.
2. Those permit conditions that have been modified or revised by this permitting action are identified by a date citation located directly under the permit condition and on the right hand margin.
3. This PTC permit is a modification of the following permit:
 - Tier II Operating Permit No. T2-020412, issued on February 24, 2009.
4. The emission sources regulated by this permit are listed in the following table.

Table 1 REGULATED SOURCES

Source Descriptions	Emission Controls
Paint Booth No.1:	Paint Booth Filters
Paint Booth No.2:	Paint Booth Filters
Space Heaters	N/A
Welding Operations	N/A

PAINT BOOTHS NO. 1 AND 2

Process Description

5. Process Description

Paint booth No. 1 is primarily used to apply coating to cargo trailer frames. The cargo frames are coated with primer and topcoat coating mixtures. Paint booth No. 1 has one stack and has been in operation since 1979.

Paint booth No. 2 is primarily used to apply coating to horse trailer frames. The horse trailer frames are coated with primer and topcoat coating mixtures. Paint booth No. 2 has two stacks and has been in operation since 1986.

6. Emission Controls Description

Table 2 PAINT BOOTHS NO. 1 AND NO. 2 DESCRIPTIONS

Emissions Units / Processes	Emission Control Devices	Emission Points
<u>Paint Booth No.1:</u> Paint booth No. 1 has been in operation since 1979 and is used to apply primer (primer paint, catalyst, and reducer) and a topcoat coatings to trailer frames. This booth has one exhaust stack. <u>Paint Booth No.2:</u> Paint booth No. 2 has been in operation since 1986 to apply primer (primer paint, catalyst, and reducer) and a topcoat coating to trailer frames. This booth has two identical exhaust stacks.	<u>Paint Booth No.1:</u> Manufacturer: Superior Glass Fibers, Inc. Type: Glass Fiber Paint Arrestor P Model: TYB 26-300-22-00 Filters PM ₁₀ Control Efficiency: 96% <u>Paint Booth No.2:</u> Manufacturer: Superior Glass Fibers, Inc. Type: Glass Fiber Paint Arrestor P Model: TYB 26-300-22-C-4-00 Filters PM ₁₀ Control Efficiency: 96%	Vent C
<u>Space Heaters:</u> Two heaters with a rated heat input of 300,000 Btu/hr One heater with a rated heat input of 125,000 Btu/hr Thirteen heaters with a rated heat input of 80,000 Btu/hr Ten heaters with a rated heat input of 75,000 Btu/hr Two heaters with a rated heat input of 90,000 Btu/hr Four heaters with a rated heat input of 100,000 Btu/hr	N/A	Vents A and B
Space Heaters	N/A	32 space heater outlets
Welding Operations	N/A	Fugitive

Emission Limits

7. Emission Limits

The emissions from the Paint Booth No. 1 and No.2 stacks shall not exceed any emissions rate limit in the following table.

Table 3 PAINT BOOTHS NO. 1 AND NO. 2 EMISSION LIMITS^a

Emissions Unit	PM ₁₀ ^b		SO ₂ ^b		NO _x ^b		CO ^b		VOC ^b	
	lb/hr ^c	T/yr ^d	lb/hr ^c	T/yr ^d	lb/hr ^c	T/yr ^d	lb/hr ^c	T/yr ^d	lb/hr ^c	T/yr ^d
Paint Booth No.1 and No.2 combined	1.24	5.43	N/A	N/A	N/A	N/A	N/A	N/A	7.325	32.1
Space Heaters	N/A	0.1	N/A	0.008	N/A	1.25	N/A	0.53	N/A	0.073
Welding Operations	N/A	0.027	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

- a) In absence of any other credible evidence, compliance is assured by complying with permit operating, monitoring, and record keeping requirements.
- b) Particulate matter with an aerodynamic diameter less than or equal to a nominal ten (10) micrometers, including condensable particulate as defined in IDAPA 58.01.01.006.81.
- c) Pounds per hour, as determined by a test method prescribed by IDAPA 58.01.01.157, EPA reference method, or DEQ-approved alternative.
- d) Tons per any consecutive 12-calendar month period.

8. HAPs Emissions Limits

Emissions of HAPs from the trailer coating process, including but not limited to HAPs emissions from thinner, reducer, primer, top coat, clear coat, activator, retarder, accelerator, and hardener, shall not exceed either 10 T/yr for any one HAP or 16.53 T/yr for all HAPs combined.

[January 6, 2010]

9. TAPs Emissions Limits

Emissions of TAPs from the trailer coating process, including but not limited to TAPs emissions from thinner, reducer, primer, top coat, clear coat, activator, retarder, accelerator, and hardener, shall not exceed either the EL (lb/hr) (for TAPs listed in both IDAPA 58.01.01.585 and 586) or the AAC (mg/m³) (for TAPs listed in IDAPA 58.01.01.585) or the AACC (µg/m³) (for TAPs listed in IDAPA 58.01.01.586).

[January 6, 2010]

10. Opacity Limit

Emissions from the Paint Booth No. 1 and No.2 stacks, or any other stack, vent, or functionally equivalent openings associated with the Paint Booth No. 1 and No.2, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

11. Odors

The permittee shall not allow, suffer, cause, or permit the emission of odorous gases, liquids, or solids into the atmosphere of such nature and duration and under such conditions as would be injurious to human health or welfare, to animal or plant life, or to property, or to interfere unreasonably with the enjoyment of life or property in accordance with IDAPA 58.01.01.776.

Operating Requirements

12. Paint Booth Filter System

The permittee shall monitor and record visible emissions from the spray booth filter system **once per day** when operating (for any day that a coating operation is performed in the paint spray booths) to demonstrate compliance with the opacity limit Permit Condition. The inspection shall consist of a see/no see evaluation for the paint spray booth exhaust system. If any visible emissions are present from the paint spray booth exhaust system, the permittee shall either take appropriate corrective action as expeditiously as practicable, or perform a Method 9 opacity test in accordance with the procedures outlined in IDAPA 58.01.01.625. A minimum of 30 observations shall be recorded when conducting the opacity test. If opacity is greater than 20% for a period or periods aggregating more than three minutes in any 60-minute period, the permittee shall take all necessary corrective action and report the exceedance in accordance with IDAPA 58.01.01.130-136.

The permittee shall maintain records of the results of each visible emissions inspection and each opacity test when conducted. The records shall include, at a minimum, the date and results of each inspection and opacity test and a description of the following: the permittee's assessment of the conditions existing at the time visible emissions are present (if observed), any corrective action taken in response to the visible emissions, and the date corrective action was taken.

[January 6, 2010]

13. Baghouse/Filter System Procedures

Within 60 days of permit issuance, the permittee shall have developed a Baghouse/Filter System Procedures document for the inspection and operation of the baghouses/filter system which controls emissions from the paint booth filter system. The Baghouse/Filter System Procedures document shall be a permittee developed document independent of the manufacturer supplied operating manual but may include summaries of procedures included in the manufacturer supplied operating manual.

The Baghouse/Filter System Procedures document shall describe the procedures that will be followed to comply with the General Compliance General Provision and shall contain requirements for **daily** see-no-see visible emissions inspections of the baghouse. The inspection shall occur during daylight hours and under normal operating conditions.

The Baghouse/Filter System Procedures document shall also include a schedule and procedures for corrective action that will be taken if visible emissions are present from the baghouse at anytime. At a minimum the document shall include:

- procedures to determine if bags or cartridges are ruptured; and
- procedures to determine if bags or cartridges are not appropriately secured in place.

The Permittee shall maintain records of the results of each baghouse/filter system inspections in accordance with the Recordkeeping General Provision. The records shall include a description of whether visible emissions were present and if visible emissions were present a description of the corrective action that was taken.

The Baghouse/Filter System Procedures document shall be submitted to DEQ within 60 days of permit issuance for review and comment and shall contain a certification by a responsible official. Any changes to the Baghouse/Filter System Procedures document shall be submitted within 15 days of the change.

The Baghouse/Filter System Procedures document shall also remain on site at all times and shall be made available to DEQ representatives upon request.

The operating and monitoring requirements specified in the Baghouse/Filter System Procedures document are incorporated by reference to this permit and are enforceable permit conditions.

[January 6, 2010]

14. Allowable Fuel Types

The space heaters shall only combust natural gas as fuel.

[January 6, 2010]

15. Prohibition From Using MeCl to Remove Paint

The permittee shall not use Methylene Chloride (MeCl) to remove paint at this facility.

[January 6, 2010]

16. Spray Gun and Spray Booth Filter System

- All painting at this facility, including application of primer, shall be conducted inside the booth with filters in place, fan(s) operating, and door(s) closed.
- All painting shall be conducted with a HVLP spray gun with a minimum 65% transfer efficiency.
- The permittee shall install, maintain, and operate according to the manufacturer's specifications and recommendations, a spray booth filter system with a minimum capture efficiency of 96% for PM₁₀ emissions.

[January 6, 2010]

17. 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, General Compliance Requirements

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- The permittee shall meet the requirements of 40 CFR 63.11173(e)(1). All painters must be certified that they have completed training in the proper spray application of surface coatings and the proper setup and maintenance of spray equipment. The minimum requirements for training and certification are described in 40 CFR 63.11173(f). The spray application of surface coatings is prohibited by persons who are not certified as having completed the training described in 40 CFR 63.11173(f).
- All spray-applied coatings must be applied in a spray booth, preparation station, or mobile enclosure that meets the requirements of 40 CFR 63.11173(e)(2).
 - All spray booths, preparation stations, and mobile enclosures must be fitted with a type of filter technology that is demonstrated to achieve at least 98% capture of paint overspray. The procedure used to demonstrate filter efficiency must be consistent with the American Society of Heating, Refrigerating, and Air-Conditioning Engineers (ASHRAE) Method 52.1.
 - Spray booths and preparation stations used to refinish complete motor vehicles or mobile equipment must be fully enclosed with a full roof, and four complete walls or complete side curtains, and must be ventilated at negative pressure so that air is drawn into any openings in the booth walls or preparation station curtains. However, if a spray booth is fully enclosed and has seals on all doors and other openings and has an automatic pressure balancing system, it may be operated at up to, but not more than, 0.05 inches water gauge positive pressure.
 - Spray booths and preparation stations that are used to coat miscellaneous parts and products or vehicle subassemblies must have a full roof, at least three complete walls or complete side curtains, and must be ventilated so that air is drawn into the booth. The walls and roof of a booth may have openings, if needed, to allow for conveyors and parts to pass through the booth during the coating process.

- All spray-applied coatings must be applied with a high volume, low pressure (HVLV) spray gun, electrostatic application, airless spray gun, or air-assisted airless spray gun, in accordance with 40 CFR 63.11173(e)(3).
- All paint spray gun cleaning must be done so that an atomized mist or spray of gun cleaning solvent and paint residue is not created outside of a container that collects used gun cleaning solvent, in accordance with 40 CFR 63.11173(e)(4). Spray gun cleaning may be done by using a fully enclosed spray gun washer.
- Each owner or operator must ensure and certify that all new and existing personnel, including contract personnel, who spray apply surface coatings, as defined in 40 CFR 63.11180, are trained in the proper application of surface coatings as required by 40 CFR 63.11173(e)(1), in accordance with 40 CFR 63.11173(f). The training program must include, at a minimum:
 - A list of all current personnel by name and job description who are required to be trained;
 - Hands-on and classroom instruction that addresses, at a minimum, initial and refresher training in the following topics:
 - Spray gun equipment selection, set up, and operation, including measuring coating viscosity, selecting the proper fluid tip or nozzle, and achieving the proper spray pattern, air pressure and volume, and fluid delivery rate;
 - Spray technique for different types of coatings to improve transfer efficiency and minimize coating usage and overspray, including maintaining the correct spray gun distance and angle to the part, using proper banding and overlap, and reducing lead and lag spraying at the beginning and end of each stroke;
 - Routine spray booth and filter maintenance, including filter selection and installation; and
 - Environmental compliance with the requirements of 40 CFR 63, Subpart HHHHHH.
 - A description of the methods to be used at the completion of initial or refresher training to demonstrate, document, and provide certification of successful completion of the required training.
- All new and existing personnel at the facility, including contract personnel, who spray apply surface coatings, as defined in 40 CFR 63.11180, must be trained by the dates specified in 40 CFR 63.11173(g). Employees who transfer within a company to a position as a painter are subject to the same requirements as a new hire.
 - All personnel must be trained and certified no later than 180 days after hiring. Painter training that was completed within five years prior to the date training is required, and that meets the requirements specified in 40 CFR 63.11173(f)(2) of this section satisfies this requirement and is valid for a period not to exceed five years after the date the training is completed.
 - Training and certification will be valid for a period not to exceed five years after the date the training is completed, and all personnel must receive refresher training that meets the requirements of this section and be re-certified every five years.
- The parts of the General Provisions which apply to the permittee are specified in Table 4, in accordance with 40 CFR 63.11174(a).

Table 4 APPLICABILITY OF GENERAL PROVISIONS TO SUBPART HHHHHH OF PART 63

Citation	Subject	Explanation
40 CFR 63.1(a)(1)-(12)	General Applicability	
40 CFR 63.1(b)(1)-(3)	Initial Applicability Determination	Applicability of subpart HHHHHH is also specified in 40 CFR 63.11170.
40 CFR 63.1(c)(1)	Applicability After Standard Established	
40 CFR 63.1(c)(2)	Applicability of Permit Program for Area Sources	
40 CFR 63.1(c)(5)	Notifications	
40 CFR 63.2	Definitions	Additional definitions are specified in 40 CFR 63.11180.
40 CFR 63.3(a)-(c)	Units and Abbreviations	
40 CFR 63.4(a)(1)-(5)	Prohibited Activities	
40 CFR 63.4(b)-(c)	Circumvention/Fragmentation	
40 CFR 63.6(a)	Compliance With Standards and Maintenance Requirements—Applicability	
40 CFR 63.6(b)(1)-(7)	Compliance Dates for New and Reconstructed Sources	40 CFR 63.11172 specifies the compliance dates.
40 CFR 63.6(c)(1)-(5)	Compliance Dates for Existing Sources	40 CFR 63.11172 specifies the compliance dates.
40 CFR 63.6(e)(1)-(2)	Operation and Maintenance	
40 CFR 63.6(f)(1)	Compliance Except During Startup, Shutdown, and Malfunction	
40 CFR 63.6(f)(2)-(3)	Methods for Determining Compliance	
40 CFR 63.6(g)(1)-(3)	Use of an Alternative Standard	
40 CFR 63.6(i)(1)-(16)	Extension of Compliance	
40 CFR 63.6(j)	Presidential Compliance Exemption	
40 CFR 63.9(a)-(d)	Notification Requirements	40 CFR 63.11175 specifies notification requirements.
40 CFR 63.9(i)	Adjustment of Submittal Deadlines	
40 CFR 63.9(j)	Change in Previous Information	40 CFR 63.11176(a) specifies the dates for submitting the notification of changes report.
40 CFR 63.10(a)	Recordkeeping/Reporting—Applicability and General Information	
40 CFR 63.10(b)(1)	General Recordkeeping Requirements	Additional requirements are specified in 40 CFR 63.11177.
40 CFR 63.10(b)(2)(xii)	Waiver of recordkeeping requirements	
40 CFR 63.10(b)(2)(xiv)	Records supporting notifications	
40 CFR 63.10(b)(3)	Recordkeeping Requirements for Applicability Determinations	

Table 4 APPLICABILITY OF GENERAL PROVISIONS TO SUBPART HHHHHH OF PART 63 (Continued)

Citation	Subject	Explanation
40 CFR 63.10(d)(1)	General Reporting Requirements	Additional requirements are specified in 40 CFR 63.11176.
40 CFR 63.10(d)(4)	Progress Reports for Sources With Compliance Extensions	
40 CFR 63.10(f)	Recordkeeping/Reporting Waiver	
40 CFR 63.12	State Authority and Delegations	
40 CFR 63.13	Addresses of State Air Pollution Control Agencies and EPA Regional Offices	
40 CFR 63.14	Incorporation by Reference	Test methods for measuring paint booth filter efficiency and spray gun transfer efficiency in 40 CFR 63.11173(e)(2) and (3) are incorporated and included in 40 CFR 63.14.
40 CFR 63.15	Availability of Information/Confidentiality	
40 CFR 63.16(a)	Performance Track Provisions—reduced reporting	

[January 6, 2010]

Monitoring and Recordkeeping Requirements

18. Odor Complaints

The permittee shall maintain records of all odor complaints received to demonstrate compliance with the odors Permit Condition. The permittee shall take appropriate corrective action as expeditiously as practicable. The records shall include, at a minimum, the date each complaint was received and a description of the following: the complaint, the permittee’s assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.

[January 6, 2010]

19. Material Purchase Records and Material Data Safety Sheets

For each material used in the trailer coating process, including but not limited to thinner, reducer, primer, top coat, clear coat, activator, retarder, accelerator, and hardener the permittee shall record and maintain the following records:

- Material purchase records
- Material Safety Data Sheets (MSDS)

[January 6, 2010]

20. Material Usage Records

The permittee shall monitor and record daily, in gallons, the usage of all materials used in the trailer coating process including but not limited to thinner, reducer, primer, top coat, clear coat, activator, retarder, accelerator, and hardener.

[January 6, 2010]

21. PM₁₀ Emissions Monitoring Requirements

Using the purchase records, MSDSs, and material usage records, the permittee shall monitor and record the monthly and annual PM₁₀ emissions in tons from the trailer coating process in order to demonstrate compliance with the emissions limits Permit Condition.

Monthly PM₁₀ emissions shall be calculated for each material as follows:

Total monthly PM₁₀ emissions = {Percent solids content (material #1) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1) x [100 – (paint gun percent transfer efficiency) ÷ 100]} x [100 – (paint booth filters PM₁₀ percent control efficiency) ÷ 100]} ÷ 2,000 pounds per ton + ... + {Percent solids content (material #n) ÷ 100 x Density in pounds per gallon (material #n) x monthly usage in gallons (material #n) x [100 – (paint gun percent transfer efficiency) ÷ 100]} x [100 – (paint booth filters PM₁₀ percent control efficiency) ÷ 100]} ÷ 2,000 pounds per ton

Annual PM₁₀ emissions shall be determined by summing total monthly PM₁₀ emissions over each previous consecutive 12-month period.

[January 6, 2010]

22. VOC Emissions Monitoring Requirements

Using the purchase records, MSDSs, and material usage records, the permittee shall monitor and record the monthly and annual VOC emissions in tons from the trailer coating process in order to demonstrate compliance with the emissions limits Permit Condition.

Monthly VOC emissions shall be calculated for each material as follows:

Total monthly VOC emissions = [Percent VOC content (material #1) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + ... + [Percent VOC content (material #n) ÷ 100 x Density in pounds per gallon (material #n) x monthly usage in gallons (material #n)] ÷ 2,000 pounds per ton

Annual VOC emissions shall be determined by summing total monthly VOC emissions over each previous consecutive 12-month period.

[January 6, 2010]

23. HAPs Emissions Monitoring Requirements

Using the purchase records, MSDSs, and material usage records, the permittee shall monitor and record the monthly and annual HAPs (as defined in IDAPA 58.01.01.006) emissions in tons from the trailer coating process in order to demonstrate compliance with the emissions limits Permit Condition.

Monthly HAPs emissions shall be calculated for each HAP for each material as follows:

Total monthly HAPs emissions = [Percent HAP #1 content (material #1) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + [Percent HAP #2 content (material #1) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + ... + [Percent HAP #n content (material #1) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + ... + [Percent HAP #1 content (material #n) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + [Percent HAP #2 content (material #n) ÷ 100 x Density in pounds per gallon (material #1) x monthly usage in gallons (material #1)] ÷ 2,000 pounds per ton + ... + [Percent HAP #n content (material #n) ÷ 100 x Density in pounds per gallon (material #n) x monthly usage in gallons (material #n)] ÷ 2,000 pounds per ton

Annual HAPs emissions shall be determined by summing total monthly HAPs emissions over each previous consecutive 12-month period.

[January 6, 2010]

24. TAPs Emissions Monitoring Requirements

Using the purchase records, MSDSs, and material usage records, the permittee shall monitor and record the individual hourly TAPs (as specified in IDAPA 58.01.01.585 and 586) emissions from the trailer coating process in order to demonstrate compliance with the TAPs emissions limits Permit Condition.

Each individual hourly TAPs emissions (except for chromium, lead, manganese, nickel, or cadmium because they are regulated by HHHHHH) shall be calculated for each material as follows:

$$\text{Hourly TAPs emissions} = [\text{Percent TAP \#1 content (material \#1)} \div 100 \times \text{Density in pounds per gallon (material \#1)} \times \text{daily usage in gallons (material \#1)} \div 24 \text{ hours/day}]$$

If any of the individual hourly TAPs emissions limits exceed the screening emissions level (EL) specified in IDAPA 58.01.01.585 and 586, a modeling demonstration shall be conducted to demonstrate compliance with the AAC (mg/m^3) (for TAPs listed in IDAPA 58.01.01.585) or the AACC ($\mu\text{g/m}^3$) (for TAPs listed in IDAPA 58.01.01.586).

[January 6, 2010]

25. 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Recordkeeping

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- The permittee shall keep the following records in accordance with 40 CFR 63.11177(a) through (d) and (h).
 - Certification that each painter has completed the training specified in 40 CFR 63.11173(f) with the date the initial training and the most recent refresher training was completed.
 - Documentation of the filter efficiency of any spray booth exhaust filter material, according to the procedure in 40 CFR 63.11173(e)(2).
 - Copies of any notification submitted as required by 40 CFR 63.11175 and copies of any report submitted as required by 40 CFR 63.11176.
 - Records of any deviation from the requirements in 40 CFR 63.11173, 63.11174, 63.11175, or 63.11176. These records must include the date and time period of the deviation, and a description of the nature of the deviation and the actions taken to correct the deviation.
 - Records of any assessments of source compliance performed in support of the initial notification, notification of compliance status, or annual notification of changes report.
- The permittee shall maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record in accordance with 40 CFR 63.11178(a). Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period.
- In accordance with 40 CFR 63.11178(a), the permittee shall maintain copies of the records specified in 40 CFR 63.11177 for a period of at least five years after the date of each record. Copies of records must be kept on site and in a printed or electronic form that is readily accessible for inspection for at least the first two years after their date, and may be kept off-site after that two year period.

26. Incorporation of Federal Requirements by Reference

Unless expressly provided otherwise, any reference in this permit to any document identified in IDAPA 58.01.01.107.03 shall constitute the full incorporation into this permit of that document for the purposes of the reference, including any notes and appendices therein. Documents include, but are not limited to:

- National Emission Standards for Hazardous Air Pollutants (NESHAP) Area Sources, 40 CFR Part 63, Subpart HHHHHH.

For permit conditions referencing or cited in accordance with any document incorporated by reference (including permit conditions identified as NESHAP), should there be any conflict between the requirements of the permit condition and the requirements of the document, the requirements of the document shall govern, including any amendments to that regulation.

[January 6, 2010]

27. Recordkeeping

The permittee shall comply with the recordkeeping requirements General Provision.

[January 6, 2010]

Reporting Requirements

28. 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Notifications

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH.

- Initial Notification. The permittee must submit the initial notification required by 40 CFR 63.9(b) in accordance with 40 CFR 63.11175(a). For this existing source, you must submit the Initial Notification no later than January 11, 2010. The initial notification must provide the following information.
 - The company name, if applicable;
 - The name, title, street address, telephone number, e-mail address (if available), and signature of the owner and operator, or other certifying company official;
 - The street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
 - An identification of the relevant standard, such as 40 CFR part 63, Subpart HHHHHH;
 - A brief description of the type of operation. For all surface coating operations, indicate whether the source is a motor vehicle and mobile equipment surface coating operation or a miscellaneous surface coating operation, and include the number of spray booths and preparation stations, and the number of painters usually employed at the operation.
 - A statement of whether the source is already in compliance with each of the relevant requirements of this subpart, or whether the source will be brought into compliance by the compliance date.

- The permittee must certify in the initial notification whether the source is in compliance with each of the requirements of 40 CFR 63, Subpart HHHHHH. If the permittee is certifying in the initial notification that the source is in compliance with the relevant requirements of this subpart, then include also a statement by a responsible official with that official's name, title, phone number, e mail address (if available) and signature, certifying the truth, accuracy, and completeness of the notification, a statement that the source has complied with all the relevant standards of this subpart, and that this initial notification also serves as the notification of compliance status.
- Notification of Compliance Status. The permittee is not required to submit a separate notification of compliance status in addition to the initial notification provided the permittee was able to certify compliance on the date of the initial notification as part of the initial notification, and the permittee's compliance status has not since changed in accordance with 40 CFR 63.11175(b). The permittee must submit a Notification of Compliance Status by March 11, 2011. The permittee is required to submit the following information with the Notification of Compliance Status:
 - The company's name and the street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
 - The name, title, address, telephone, e-mail address (if available) and signature of the owner and operator, or other certifying company official, certifying the truth, accuracy, and completeness of the notification and a statement of whether the source has complied with all the relevant standards and other requirements of this subpart or an explanation of any noncompliance and a description of corrective actions being taken to achieve compliance. For surface coating operations, the relevant requirements are specified in 40 CFR 63.11173(e) through (g).
 - The date of the Notification of Compliance Status.

[January 6, 2010]

29. 40 CFR 63, Subpart HHHHHH – MACT Standards and Management Practices for Paint Stripping and Miscellaneous Surface Coating Operations, Reports

Unless an exemption from the EPA has been granted to this facility in accordance with 40 CFR 63.11170 (a)(2), in accordance with 40 CFR 63.11172(a)(2), on and after January 10, 2011 the permittee shall comply with the applicable emission limitations and requirements of the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH

- Annual Notification of Changes Report. In accordance with 40 CFR 63.11176, the permittee is required to submit a report in each calendar year in which information previously submitted in either the initial notification required by 40 CFR 63.11175(a), Notification of Compliance, or a previous annual notification of changes report submitted has changed. Deviations from the relevant requirements in 40 CFR 63.11173(a) through (d) or 40 CFR 63.11173(e) through (g) on the date of the report will be deemed to be a change. The annual notification of changes report must be submitted prior to March 1 of each calendar year when reportable changes have occurred and must include the following information.
 - The company's name and the street address (physical location) of the affected source and the street address where compliance records are maintained, if different.
 - The name, title, address, telephone, e-mail address (if available) and signature of the owner and operator, or other certifying company official, certifying the truth, accuracy, and completeness of the notification and a statement of whether the source has complied with all the relevant standards and other requirements of this subpart or an explanation of any noncompliance and a description of corrective actions being taken to achieve compliance.

- Any notifications or reporting required by the National Emission Standards for Hazardous Air Pollutants: Paint Stripping and Miscellaneous Surface Coating Operations at Area Sources, 40 CFR 63, Subpart HHHHHH or Subpart A – General Provisions shall be submitted to both of the following addresses in accordance with 40 CFR 63.13:

EPA Region 10
Director, Office of Air Quality
1200 Sixth Avenue
(OAQ-107)
Seattle, WA 98101

And,

Air Quality Permit Compliance
Department of Environmental Quality
Twin Falls Regional Office
1363 Fillmore Ct.
Twin Falls, ID 83301
Phone: (208) 736-2190
Fax: (208) 736-2194

[January 6, 2010]

PERMIT TO CONSTRUCT GENERAL PROVISIONS

General Compliance

30. The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the Rules for the Control of Air Pollution in Idaho. The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit and the Rules for the Control of Air Pollution in Idaho, and the Environmental Protection and Health Act, Idaho Code §39-101, et seq.

[Idaho Code §39-101, et seq.]

31. The permittee shall at all times (except as provided in the Rules for the Control of Air Pollution in Idaho) maintain in good working order and operate as efficiently as practicable, all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.

[IDAPA 58.01.01.211, 5/1/94]

32. Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules and regulations.

[IDAPA 58.01.01.212.01, 5/1/94]

Inspection and Entry

33. Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:

- Enter upon the permittee's premises where an emissions source is located or emissions related activity is conducted, or where records are kept under conditions of this permit;
- Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
- Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
- As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

[Idaho Code §39-108]

Construction and Operation Notification

34. The permittee shall furnish DEQ written notifications as follows in accordance with IDAPA 58.01.01.211:

- A notification of the date of initiation of construction, within five working days after occurrence;
- A notification of the date of any suspension of construction, if such suspension lasts for one year or more;
- A notification of the anticipated date of initial start-up of the stationary source or facility not more than sixty days or less than thirty days prior to such date;
- A notification of the actual date of initial start-up of the stationary source or facility within fifteen days after such date; and
- A notification of the initial date of achieving the maximum production rate, within five working days after occurrence - production rate and date.

Performance Testing

35. If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ, at its option, may have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.
36. All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.
37. Within 30 days following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The written report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00]

Monitoring and Recordkeeping

38. The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Records of monitoring information shall include, but not be limited to the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records and all original strip-chart recordings for continuous monitoring instrumentation and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

Excess Emissions

39. The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130-136 for excess emissions due to startup, shutdown, scheduled maintenance, safety measures, upsets and breakdowns.

[IDAPA 58.01.01.130-136, 4/5/00]

Certification

40. All documents submitted to DEQ, including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

False Statements

41. No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit, or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.125, 3/23/98]

Tampering

42. No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.
[IDAPA 58.01.01.126, 3/23/98]

Transferability

43. This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.
[IDAPA 58.01.01.209.06, 4/11/06]

Severability

44. The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.
[IDAPA 58.01.01.211, 5/1/94]