



STATE OF IDAHO  
DEPARTMENT OF  
ENVIRONMENTAL QUALITY

1410 North Hilton • Boise, Idaho 83706 • (208) 373-0502  
www.deq.idaho.gov

C.L. "Butch" Otter, Governor  
John H. Tippets, Director

August 16, 2018

Douglas Losee, V.P. Environmental  
Covia Holdings Corporation  
121 St. Andrews Court  
Mankato, MN 56001

RE: Facility ID No. 045-00003, Project No. 62095, Covia Holdings Corporation, Emmett  
Facility Name Change by Permit to Construct Revision

Dear Mr. Losee:

The Department of Environmental Quality (DEQ) is issuing Permit to Construct (PTC) No. P-2017.0004, Project 62095 to change the name of the facility from Unimin Corp. to Covia Holdings Corporation. This PTC is issued in accordance with IDAPA 58.01.01.209.04 of the Rules for the Control of Air Pollution in Idaho and is based on the certified information received on August 3, 2018. The facility name change is based on the following information:

**Previous Facility Information**

Permittee:	Unimin Corp.
Mailing Address:	4601 Cascade Road, Emmett, ID 83612
Facility Location:	4601 Cascade Road, Emmett, ID 83612
Facility Contact:	Kerry Kelley, Plant Manager
Phone Number:	(208) 365-7153
E-mail Address:	kkelley@unimin.com
Responsible Official:	Douglas Losee, V.P. Environmental Affairs
Phone Number:	(440) 279-0245

**Updated Facility Information**

Permittee:	Covia Holdings Corporation
Mailing Address:	121 St. Andrews Court, Mankato, MN 56001
Facility Location:	4601 Cascade Road, Emmett, ID 83612
Facility Contact:	Kerry Kelley, Plant Manager
Phone Number:	(208) 365-7153
E-mail Address:	Kerry.Kelley@coviacorp.com
Responsible Official:	Douglas Losee, V.P. Environmental
Phone Number:	(440) 279-0245

Covia Holdings Corporation, Emmett  
August 16, 2018  
Page 2 of 2

This permit is effective immediately and replaces PTC No. P-2017.0004, Project 61839, issued March 3, 2017. This permit does not release Covia Holdings Corporation from compliance with all other applicable federal, state, or local laws, regulations, permits, or ordinances.

In order to fully understand the compliance requirements of this permit, DEQ highly recommends that you schedule a meeting with Tom Krinke, AQ Compliance Officer, at (208) 373-0419 to review and discuss the terms and conditions of this permit. Should you choose to schedule this meeting, DEQ recommends that the following representatives attend the meeting: your facility's plant manager, responsible official, environmental contact, and any other staff responsible for day-to-day compliance with permit conditions.

If you have any questions, please contact Kelli Wetzel at (208) 373-0502 or [kelli.wetzel@deq.idaho.gov](mailto:kelli.wetzel@deq.idaho.gov).

Sincerely,



Mike Simon  
Stationary Source Program Manager  
Air Quality Division

Attachment

MS/kw            Permit No. P-2017.0004 PROJ 62095

## Air Quality

### PERMIT TO CONSTRUCT

---

<b>Permittee</b>	Covia Holdings Corporation
<b>Permit Number</b>	P-2017.0004
<b>Project ID</b>	62095
<b>Facility ID</b>	045-00003
<b>Facility Location</b>	4601 Cascade Road Emmett, ID 83612

### Permit Authority


This permit (a) is issued according to the "Rules for the Control of Air Pollution in Idaho" (Rules), IDAPA 58.01.01.200-228; (b) pertains only to emissions of air contaminants regulated by the State of Idaho and to the sources specifically allowed to be constructed or modified by this permit; (c) has been granted on the basis of design information presented with the application; (d) does not affect the title of the premises upon which the equipment is to be located; (e) does not release the permittee from any liability for any loss due to damage to person or property caused by, resulting from, or arising out of the design, installation, maintenance, or operation of the proposed equipment; (f) does not release the permittee from compliance with other applicable federal, state, tribal, or local laws, regulations, or ordinances; and (g) in no manner implies or suggests that the Idaho Department of Environmental Quality (DEQ) or its officers, agents, or employees assume any liability, directly or indirectly, for any loss due to damage to person or property caused by, resulting from, or arising out of design, installation, maintenance, or operation of the proposed equipment. Changes in design, equipment, or operations may be considered a modification subject to DEQ review in accordance with IDAPA 58.01.01.200-228.

**Date Issued** August 16, 2018



*Kelli Wetzel*

Kelli Wetzel, Permit Writer



*Mike Simon*

Mike Simon, Stationary Source Manager

## Contents

1	Permit Scope.....	3
2	Facility-Wide Conditions.....	4
3	Dust Collector DC-03.....	6
4	Dust Collectors DC-01, DC-02, and DC-04.....	8
5	Ball Mill BM-01; Belt Conveyor BC-12 and Cam Belt CB-01.....	10
6	Wet Plant Feeder and Processing; Dryer Feeding Operation.....	11
7	Loadout Operation.....	13
8	General Provisions.....	14

# 1 Permit Scope

## Purpose

- 1.1 This is a revised permit to construct (PTC) to change the name from Unimin Corp. to Covia Holdings Corporation.
- 1.2 This PTC replaces Permit to Construct No. P-2017.0004 issued on March 3, 2017.

## Regulated Sources

Table 1.1 lists all sources of regulated emissions in this permit.

**Table 1.1 Regulated Sources**

Permit Section	Source	Control Equipment
3	Dryer DR-01, Starkaire 10' diameter with Maxon gas burner Installed before 9/23/83	Wet Scrubber DC-03 BACT model ME-V21
4	Vibrating screens VS-10 and VS-11, Derrick model K48-96A-3SM Screw conveyors SC-03 and SC-04 Bucket elevators BE-01, BE-02, and BE-03; installed before 9/23/83 Screens VS-14 and VS-15, Derrick model K48-120A-2S; installed after 6/3/97	Wet Scrubber DC-01 BACT model MEV-12, 12,000 acfm
4	Coarse screens VS-01 and VS-02, Derrick model 48-96A-3SM; installed before 4/28/67 Coarse screens VS-03 and VS-04, Derrick model 48-96A-2S; installed 5/2/67 Coarse screen VS-05, Derrick model K-48-120A-2S; installed 5/2/67 Coarse screen VS-06, Derrick model K24-48A-2S Coarse screens VS-07 and VS-08, Derrick model K48-120A-3SM; installed 4/17/86 Coarse screen VS-09, Derrick model K48-96A-2S, 4 ft. x 8 ft. , installed 1/16/70 Bucket elevators BE-04 and BE-05, respectively; installed before 9/23/83 Bins BN-01 to BN-11; Installed before 9/23/83 Belt conveyors BC-05, BC-06, and BC-10; installed before 9/23/83 Screw conveyors SC-05, SC-06, SC-07, and SC-08	Wet scrubber DC-02 Riley model A-33-14
4	Sand baggers BA-01 and BA-02 and BA-02B, St. Regis Jr. Force Flow; installed before 9/23/83 Sand bagger BA-03, Unimin; installed before 9/23/92 Belt conveyors BC-06 and BC-07; installed before 9/23/83 Hoppers HO-05 and HO-06	Wet scrubber DC-04 BACT model ME-V006, 6,000 acfm
5	Ball mill BM-01, Allis Chalmers, installed 12/31/88 Cam Belt CB-01 and Belt conveyor BC-12, installed 12/1/86 and before 1990, respectively	None
6	Hoppers HO-01 and HO-03, Feeder FE-01, and Cam Belt CB-01 (see above); installed before 9/23/83 Rod mill RM-01 (see above) Screens VS-12 and VS-13 Hopper HO-02, Screw conveyors SC-01 and SC-02, and Belt conveyor BC-02; all installed before 9/23/83	None
7	Hoppers HO-05 and HO-04, Belt conveyors BC-07 and BC-11 and all installed before 9/23/83	None
2	Stockpiles, roads and all other fugitive sources	Reasonable Controls

## 2 Facility-Wide Conditions

### Fugitive Emissions

- 2.1 All reasonable precautions shall be taken to prevent particulate matter (PM) from becoming airborne in accordance with IDAPA 58.01.01.650–651. In determining what is reasonable, consideration will be given to factors such as the proximity of dust-emitting operations to human habitations and/or activities and atmospheric conditions that might affect the movement of PM. Some of the reasonable precautions include, but are not limited to, the following practices, where practical:
- Use, where practical, of water or chemicals for control of dust in the demolition of existing buildings or structures, construction operations, the grading of roads, or the clearing of lands.
  - Application, where practical, of asphalt, oil, water, or suitable chemicals to, or covering of, dirt roads, material stockpiles, and other surfaces which can create dust;
  - Installation and use, where practical, of hoods, fans, and fabric filters or equivalent systems to enclose and vent the handling of dusty materials. Adequate containment methods should be employed during sandblasting or other operations;
  - Covering, where practical, of open-bodied trucks transporting materials likely to give rise to airborne dusts; and
  - Paving of roadways and their maintenance in a clean condition, where practical.
  - Prompt removal of earth or other stored material from streets, where practical.
- 2.2 The permittee shall monitor and maintain records of the frequency and the method(s) used (e.g., water, chemical dust suppressants) to reasonably control fugitive emissions.
- 2.3 The permittee shall maintain records of all fugitive dust complaints received. The permittee shall take appropriate corrective action as expeditiously as practicable after receiving a valid complaint. The records shall include, at a minimum, the date that each complaint was received and a description of the following: the complaint, the permittee's assessment of the validity of the complaint, any corrective action taken, and the date the corrective action was taken.
- 2.4 The permittee shall conduct quarterly facility wide inspection of potential sources of fugitive emissions during daylight hours and under normal operating conditions to ensure that the methods used to reasonably control fugitive emissions are effective. If fugitive emissions are not being reasonably controlled, the permittee shall take corrective action as expeditiously as practicable. The permittee shall maintain records of the results of each fugitive emissions inspection. The records shall include, at a minimum, the date of each inspection and a description of the following: the permittee's assessment of the conditions existing at the time fugitive emissions were present (if observed), any corrective action taken in response to the fugitive emissions, and the date the corrective action was taken.

## **Visible Emissions**

- 2.5 The permittee shall not discharge any air pollutant to the atmosphere from any point of emission for a period or periods aggregating more than three minutes in any 60-minute period which is greater than 20% opacity as determined by procedures contained in IDAPA 58.01.01.625. These provisions shall not apply when the presence of uncombined water, NO<sub>x</sub>, and/or chlorine gas is the only reason for the failure of the emission to comply with the requirements of this section.

## **Reports and Certifications**

- 2.6 Any reporting required by this permit—including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, notifications of intent to test, testing reports, or compliance certifications—shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete. Any reporting required by this permit shall be submitted to the following address:

Air Quality Permit Compliance  
Department of Environmental Quality  
Boise Regional Office  
1445 N. Orchard  
Boise, ID 83706  
Fax: (208) 373-0287

## **Open Burning**

- 2.7 The permittee shall comply with the “Rules for Control of Open Burning” (IDAPA 58.01.01.600–623).

## **Air Stagnation Advisory Days**

- 2.8 The permittee shall comply with the Air Pollution Emergency Rules in IDAPA 58.01.01.550 through 562.

## **Obligation to Comply**

- 2.9 Receiving a PTC permit shall not relieve any owner or operator of the responsibility to comply with all applicable local, state, and federal rules and regulations.

### 3 Dust Collector DC-03

#### 3.1 Process Description

Dryer DR-01 and Burner BU-01 are vented to the atmosphere through dust collector DC-03's stack.

#### 3.2 Control Device Descriptions

Table 3.1 Dust Collector DC-03 Description

Emissions Units / Processes	Control Devices
Dryer DR-01	Wet scrubber DC-03
Burner BU-01	

#### Emission Limits

##### 3.3 Emission Limits

The PM emissions from the Dust collector DC-03 stack shall not exceed 3.24 lb/hr and 14.2 T/yr.

##### 3.4 Opacity Limit

Emissions from the scrubber stack, or any other stack, vent, or functionally equivalent opening associated with the scrubber stack, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

#### Operating Requirements

##### 3.5 Pressure Drop Across the Dust Collector

The pressure drop across the dust collector shall be maintained with greater than 6 in. water column.

##### 3.6 Scrubbing Media Flow Rate

Water flow rate to the dust collector shall be maintained as follows: greater than or equal to 110 gpm or a water to gas ratio of 5 gpm/1,000 acfm. If the water flow is less than 110 gpm, the air flow will be measured to see if there is 5 gpm/1,000 acfm.

##### 3.7 Installation of Monitoring Equipment

The permittee shall install, calibrate, maintain, and operate, in accordance with manufacturer specifications, equipment to continuously measure the pressure differential across the dust collector, and to measure the scrubbing media flow rate to the dust collector.

##### 3.8 Fuels and Fuel Sulfur Content

The fuels burned in the dryer are limited to natural gas and No.1 and No. 2 fuel oil. The fuel sulfur content shall not exceed the following:

- ASTM Grade No. 1 – 0.3% by weight
- ASTM Grade No. 2 – 0.5% by weight

The permittee shall maintain records of the sulfur content of each fuel delivery for a period of at least five years.

The permittee shall limit the diesel use to less than 619,463 gallons per year.

## **Monitoring and Recordkeeping Requirements**

### **3.9 Pressure Drop and Scrubbing Flow Rate**

The following parameters shall be monitored and recorded.

- Pressure drop across the dust collector once on a daily basis.
- Scrubbing media flow rate to the dust collector or water to gas ratio, once on a daily basis.
- Diesel usage for the dryer on a daily and monthly basis.

## 4 Dust Collectors DC-01, DC-02, and DC-04

### 4.1 Process Description

The following emissions units are vented to the atmosphere through dust collector DC-01's stack:

- Bucket elevators BE-01, BE-02, and BE-03
- Vibrating screens VS-10, VS-11, VS-14, and VS-15
- Screw conveyors SC-03 and SC-04

The following equipment is vented through DC-02:

- Bucket elevators BE-04 and BE-05
- Nine vibrating screens VS-01 to VS-09
- 11 bins, BN-01 to BN-11
- Belt conveyors BC-05 and BC-10
- Screw conveyors SC-05, SC-06, SC-07, and SC-08

The following equipment is vented through DC-04:

- Hoppers HO-05 and HO-06
- Belt conveyors BC-06 and BC-07
- Bagging stations BA-01, BA-02, BA-02B, and BA-03

### 4.2 Control Device Descriptions

The dust collectors (DC-01, DC-02, and DC-04) are wet scrubbers.

## Emission Limits

### 4.3 Emission Limits

The emissions from the DC-01, DC-02 and DC-04 stacks shall not exceed any corresponding emissions rate limits listed in Table 4.1.

Table 4.1 DC-01, DC-02, and DC-04 Emission Limits

Source Description	PM	
	lb/hr	T/yr <sup>(b)</sup>
DC-01	1.38	6.04
DC-02	2.95	12.9
DC-04	1.18	5.18

a In absence of any other credible evidence, compliance is ensured by complying with permit operating, monitoring, and record keeping requirements.

b Tons per any consecutive 12-calendar month period.

### 4.4 Stack Concentration

Particulate matter emissions from the dust collector stacks shall not exceed 0.05 g/dscm.

#### **4.5 Opacity Limit**

Emissions from the scrubber stacks, or any other stack, vent, or functionally equivalent opening associated with the scrubbers, shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

### **Operating Requirements**

#### **4.6 Pressure Drop Across the Dust Collectors**

The pressure drop across the dust collectors shall be maintained as greater than two inches of water column for DC-02 and DC-04, and greater than 4 inches of water column for DC-01.

#### **4.7 Scrubbing Media Flow Rate**

Water flow rate to the DC-01 shall be maintained as follows: greater than or equal to 60 gpm or a water to gas ratio of 5 gpm/1,000 acfm. If the water flow is less than 60 gpm, the air flow will be measured to see if there is 5 gpm/1,000 acfm.

Water flow rate to the DC-02 shall be maintained as follows: greater than or equal to 70 gpm or a water to gas ratio of 5 gpm/1,000 acfm. If the water flow is less than 70 gpm, the air flow will be measured to see if there is 5 gpm/1,000 acfm.

Water flow rate to the DC-04 shall be maintained as follows: greater than or equal to 30 gpm or a water to gas ratio of 5 gpm/1,000 acfm. If the water flow is less than 30 gpm, the air flow will be measured to see if there is 5 gpm/1,000 acfm.

#### **4.8 Installation of Monitoring Equipment**

The permittee shall install, calibrate, maintain, and operate, in accordance with manufacturer specifications, equipment to continuously measure the pressure differential across the dust collectors, and to measure the scrubbing media flow rate to the dust collectors.

### **Monitoring and Recordkeeping Requirements**

#### **4.9 Pressure Drop and Scrubbing Flow Rate**

The following parameters shall be monitored and recorded once on a daily basis.

- Pressure drop across the dust collectors
- Scrubbing media flow rate to the dust collectors

## **5 Ball Mill BM-01; Belt Conveyor BC-12 and Cam Belt CB-01**

### **5.1 Process Description**

This emission unit consists of emission sources constructed after August 31, 1983, and is thus subject to 40 CFR Part 60, Subpart 000.

### **5.2 Control Device Descriptions**

There is no control equipment associated with these sources.

### **Emission Limits**

#### **5.3 Opacity Limit**

Fugitive emissions shall not exceed an opacity of 10% as determined by the methods in 40 CFR Part 60, Appendix A.

### **Operating Requirements**

#### **5.4 Sand Moisture Content**

The moisture content of feed sand to belt conveyor BC-12 shall be greater than 1.5% at all times.

### **Monitoring and Recordkeeping Requirements**

#### **5.5 Sand Moisture Content**

The moisture content of feed sand to belt conveyor BC-12 shall be monitored and recorded on a quarterly basis.

## **6 Wet Plant Feeder and Processing; Dryer Feeding Operation**

### **6.1 Process Description**

The wet-plant feeding equipment consists of the following:

- Hopper HO-01
- Feeder FE-01
- Cam Belt CB-01

The wet plant consists of the following:

- Ball Mill BM-01
- Vibrating Screens VS-12 and VS-13

The dryer feeding equipment consists of the following:

- Hopper HO-2 and HO-03
- Screw conveyors SC-01 and SC-02
- Belt conveyor BC-02

### **6.2 Control Device Descriptions**

There is no control equipment associated with the above listed sources.

## **Emission Limits**

### **6.3 Emission Limits**

No emission of any air pollutants shall be emitted from the wet plant.

### **6.4 Opacity Limits for Wet Plant Feeding and Dryer Feeding**

Emissions from the sand feeding to the wet plant shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

### **6.5 Wet Plant Opacity Limit**

No visible emissions shall be observed from screening, milling, transferring, conditioning, pumping, or stockpiling of sand in the wet plant.

## **Operating Requirements**

### **6.6 Sand Moisture Content**

The moisture content of feed sand to the wet plant and dryer operation shall be greater than 1.5% at all times.

### **6.7 Moisture Content in Wet Plant**

Sand in the wet-plant process shall be completely saturated with water at all times.

## **Monitoring and Recordkeeping Requirements**

### **6.8 Moisture Content of Feed Sand**

The following parameters shall be monitored and recorded on a quarterly basis.

- Moisture content of feed sand to the wet-plant process
- Moisture content of feed sand to dryer operation

## **7 Loadout Operation**

### **7.1 Process Description**

The loadout equipment consists of the following:

- Hoppers HO-04 and HO-05
- Belt conveyor BC-11
- Loading Spouts LS-01 and LS-04

### **7.2 Control Device Descriptions**

There is no control equipment associated with these sources.

## **Emission Limits**

### **7.3 Opacity Limit**

Emissions from sand loading, feeding, or conveying in the loadout operation shall not exceed 20% opacity for a period or periods aggregating more than three minutes in any 60-minute period as required by IDAPA 58.01.01.625. Opacity shall be determined by the procedures contained in IDAPA 58.01.01.625.

## **Operating Requirements**

### **7.4 Sand Moisture Content**

The moisture content of feed sand to hopper HO-04 shall be greater than 1.5% at all times.

## **Monitoring and Recordkeeping Requirements**

### **7.5 Sand Moisture Content**

The moisture content of feed sand to hopper HO-04 shall be monitored and recorded on a quarterly basis. All data shall be kept onsite for a period of five years and shall be made available to Department representatives upon request.

## 8 General Provisions

### General Compliance

8.1 The permittee has a continuing duty to comply with all terms and conditions of this permit. All emissions authorized herein shall be consistent with the terms and conditions of this permit and the "Rules for the Control of Air Pollution in Idaho." The emissions of any pollutant in excess of the limitations specified herein, or noncompliance with any other condition or limitation contained in this permit, shall constitute a violation of this permit, the "Rules for the Control of Air Pollution in Idaho," and the Environmental Protection and Health Act (Idaho Code §39-101, et seq.)

[Idaho Code §39-101, et seq.]

8.2 The permittee shall at all times (except as provided in the "Rules for the Control of Air Pollution in Idaho") maintain in good working order and operate as efficiently as practicable all treatment or control facilities or systems installed or used to achieve compliance with the terms and conditions of this permit and other applicable Idaho laws for the control of air pollution.

[IDAPA 58.01.01.211, 5/1/94]

8.3 Nothing in this permit is intended to relieve or exempt the permittee from the responsibility to comply with all applicable local, state, or federal statutes, rules, and regulations.

[IDAPA 58.01.01.212.01, 5/1/94]

### Inspection and Entry

8.4 Upon presentation of credentials, the permittee shall allow DEQ or an authorized representative of DEQ to do the following:

- Enter upon the permittee's premises where an emissions source is located, emissions-related activity is conducted, or where records are kept under conditions of this permit;
- Have access to and copy, at reasonable times, any records that are kept under the conditions of this permit;
- Inspect at reasonable times any facilities, equipment (including monitoring and air pollution control equipment), practices, or operations regulated or required under this permit; and
- As authorized by the Idaho Environmental Protection and Health Act, sample or monitor, at reasonable times, substances or parameters for the purpose of determining or ensuring compliance with this permit or applicable requirements.

[Idaho Code §39-108]

### Construction and Operation Notification

8.5 This permit shall expire if construction has not begun within two years of its issue date, or if construction is suspended for one year.

[IDAPA 58.01.01.211.02, 5/1/94]

8.6 The permittee shall furnish DEQ written notifications as follows:

- A notification of the date of initiation of construction, within five working days after occurrence; except in the case where pre-permit construction approval has been granted then notification shall be made within five working days after occurrence or within five working days after permit issuance whichever is later;
- A notification of the date of any suspension of construction, if such suspension lasts for one year or more;

- A notification of the anticipated date of initial start-up of the stationary source or facility not more than sixty days or less than thirty days prior to such date; and
- A notification of the actual date of initial start-up of the stationary source or facility within fifteen days after such date; and
- A notification of the initial date of achieving the maximum production rate, within five working days after occurrence - production rate and date.

[IDAPA 58.01.01.211.03, 5/1/94]

## Performance Testing

- 8.7 If performance testing (air emissions source test) is required by this permit, the permittee shall provide notice of intent to test to DEQ at least 15 days prior to the scheduled test date or shorter time period as approved by DEQ. DEQ may, at its option, have an observer present at any emissions tests conducted on a source. DEQ requests that such testing not be performed on weekends or state holidays.
- 8.8 All performance testing shall be conducted in accordance with the procedures in IDAPA 58.01.01.157. Without prior DEQ approval, any alternative testing is conducted solely at the permittee's risk. If the permittee fails to obtain prior written approval by DEQ for any testing deviations, DEQ may determine that the testing does not satisfy the testing requirements. Therefore, at least 30 days prior to conducting any performance test, the permittee is encouraged to submit a performance test protocol to DEQ for approval. The written protocol shall include a description of the test method(s) to be used, an explanation of any or unusual circumstances regarding the proposed test, and the proposed test schedule for conducting and reporting the test.
- 8.9 Within 60 days following the date in which a performance test required by this permit is concluded, the permittee shall submit to DEQ a performance test report. The written report shall include a description of the process, identification of the test method(s) used, equipment used, all process operating data collected during the test period, and test results, as well as raw test data and associated documentation, including any approved test protocol.

[IDAPA 58.01.01.157, 4/5/00 and 4/11/15]

## Monitoring and Recordkeeping

- 8.10 The permittee shall maintain sufficient records to ensure compliance with all of the terms and conditions of this permit. Monitoring records shall include, but not be limited to, the following: (a) the date, place, and times of sampling or measurements; (b) the date analyses were performed; (c) the company or entity that performed the analyses; (d) the analytical techniques or methods used; (e) the results of such analyses; and (f) the operating conditions existing at the time of sampling or measurement. All monitoring records and support information shall be retained for a period of at least five years from the date of the monitoring sample, measurement, report, or application. Supporting information includes, but is not limited to, all calibration and maintenance records, all original strip-chart recordings for continuous monitoring instrumentation, and copies of all reports required by this permit. All records required to be maintained by this permit shall be made available in either hard copy or electronic format to DEQ representatives upon request.

[IDAPA 58.01.01.211, 5/1/94]

## **Excess Emissions**

- 8.11 The permittee shall comply with the procedures and requirements of IDAPA 58.01.01.130–136 for excess emissions due to start-up, shut-down, scheduled maintenance, safety measures, upsets, and breakdowns.

[IDAPA 58.01.01.130–136, 4/5/00]

## **Certification**

- 8.12 All documents submitted to DEQ—including, but not limited to, records, monitoring data, supporting information, requests for confidential treatment, testing reports, or compliance certification—shall contain a certification by a responsible official. The certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document(s) are true, accurate, and complete.

[IDAPA 58.01.01.123, 5/1/94]

## **False Statements**

- 8.13 No person shall knowingly make any false statement, representation, or certification in any form, notice, or report required under this permit or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.125, 3/23/98]

## **Tampering**

- 8.14 No person shall knowingly render inaccurate any monitoring device or method required under this permit or any applicable rule or order in force pursuant thereto.

[IDAPA 58.01.01.126, 3/23/98]

## **Transferability**

- 8.15 This permit is transferable in accordance with procedures listed in IDAPA 58.01.01.209.06.

[IDAPA 58.01.01.209.06, 4/11/06]

## **Severability**

- 8.16 The provisions of this permit are severable, and if any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

[IDAPA 58.01.01.211, 5/1/94]